

(12) **United States Patent**  
**Sia**

(10) **Patent No.:** **US 10,619,625 B2**  
(45) **Date of Patent:** **Apr. 14, 2020**

(54) **POWER GENERATING WINDBAGS AND WATERBAGS**

(71) Applicant: **Yik Hei Sia, Johor Bahru (MY)**

(72) Inventor: **Yik Hei Sia, Johor Bahru (MY)**

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/298,043**

(22) Filed: **Mar. 11, 2019**

(65) **Prior Publication Data**

US 2019/0257290 A1 Aug. 22, 2019

**Related U.S. Application Data**

(63) Continuation of application No. 15/889,937, filed on Feb. 6, 2018, now Pat. No. 10,233,902, which is a (Continued)

(30) **Foreign Application Priority Data**

Apr. 26, 2012 (SG) ..... 201203067  
Apr. 19, 2013 (SG) ..... 201302987

(51) **Int. Cl.**  
**F03D 7/06** (2006.01)  
**F03D 5/00** (2006.01)  
**F03D 9/30** (2016.01)  
**F03B 17/06** (2006.01)  
**F03D 15/10** (2016.01)  
**F03D 5/02** (2006.01)  
**H02K 7/06** (2006.01)  
**H02K 7/18** (2006.01)  
**F03D 9/25** (2016.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **F03D 7/06** (2013.01); **B64C 39/022** (2013.01); **B64C 39/024** (2013.01); **F03B 17/06** (2013.01); **F03D 5/00** (2013.01); **F03D 5/02** (2013.01); **F03D 9/008** (2013.01); **F03D 9/25** (2016.05); **F03D 9/30** (2016.05); **F03D 15/10** (2016.05); **H02K 7/06** (2013.01); **H02K 7/1853** (2013.01); **B64C 2201/12** (2013.01); **F05B 2220/70** (2013.01); **F05B 2240/922** (2013.01); **F05B 2240/923** (2013.01); **F05B 2270/18** (2013.01); **F05B 2270/20** (2013.01); **Y02E 10/28** (2013.01); **Y02E 10/70** (2013.01); **Y02E 10/725** (2013.01); **Y02E 10/728** (2013.01)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,124,182 A \* 11/1978 Loeb ..... F03D 5/00 244/153 R  
2011/0266809 A1 \* 11/2011 Calverley ..... F03D 5/00 290/55


(Continued)

*Primary Examiner* — Jonathan M Dager  
*Assistant Examiner* — Garrett F Evans  
(74) *Attorney, Agent, or Firm* — K. David Crockett, Esq.; Niky Economy Syrengelas, Esq.; Crockett & Crockett, PC

(57) **ABSTRACT**

A method of using a bagged power generation system comprising windbags and waterbags integrated with drones and adapting drone technologies for harnessing wind and water power to produce electricity. An extremely scalable and environmentally friendly method, system, apparatus, equipment, techniques and ecosystem configured to produce renewable green energy with high productivity and efficiency.

**2 Claims, 20 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/630,670, filed on Jun. 22, 2017, now Pat. No. 10,113,534, which is a continuation-in-part of application No. 15/270,500, filed on Sep. 20, 2016, now Pat. No. 9,698,652, which is a continuation of application No. 14/976,855, filed on Dec. 21, 2015, now Pat. No. 9,447,775, which is a continuation-in-part of application No. 14/608,511, filed on Jan. 29, 2015, now Pat. No. 9,234,501, which is a continuation of application No. 13/870,413, filed on Apr. 25, 2013, now Pat. No. 8,963,362.

- (51) **Int. Cl.**  
*B64C 39/02* (2006.01)  
*F03D 9/00* (2016.01)

- (56) **References Cited**

U.S. PATENT DOCUMENTS

2013/0115544 A1\* 5/2013 Davidson ..... B64B 1/50  
429/505  
2014/0012433 A1\* 1/2014 Vojtech ..... B64B 1/06  
701/2

\* cited by examiner




FIG. 1A




FIG. 1B

55ag











FIG. 1C










FIG. 2I




FIG. 2C

44ab  
Station B




FIG. 2F




FIG. 2G




FIG. 2H




FIG. 2D





FIG. 2E






FIG. 3D












FIG. 3C

















FIG. 6K




FIG. 6M




FIG. 6I




FIG. 6L




FIG. 6J




FIG. 6G




FIG. 6H





FIG. 6J






FIG. 6W




FIG. 6U




FIG. 6X




FIG. 6T




FIG. 6S




FIG. 6Y





FIG. 6V





FIG. 6R









FIG. 7B

FIG. 7A







## POWER GENERATING WINDBAGS AND WATERBAGS

This application is a continuation of U.S. application Ser. No. 15/889,937, filed Feb. 6, 2018, now U.S. Pat. No. 10,233,902, which is a continuation of U.S. application Ser. No. 15/630,670, filed Jun. 22, 2017, now U.S. Pat. No. 10,113,534 which is a continuation-in-part of U.S. application Ser. No. 15/270,500, filed Sep. 20, 2016, now U.S. Pat. No. 9,698,652, which is a continuation of U.S. application Ser. No. 14/976,855, filed Dec. 21, 2015, now U.S. Pat. No. 9,447,775, which is a continuation of U.S. application Ser. No. 14/608,511, filed Jan. 29, 2015, now U.S. Pat. No. 9,234,501, which is a continuation of U.S. application Ser. No. 13/870,413, filed Apr. 25, 2013, now U.S. Pat. No. 8,963,362, which in turn claims priority to SG application no. 201302987-1, filed Apr. 19, 2013 and SG application No. 201203067-2, filed Apr. 26, 2012.

### FIELD OF THE INVENTIONS

Present invention relates to the utility purpose of deploying drones and adapting drone technologies for harnessing high altitude wind energy and deep sea ocean energy to generate renewable energy; displacing use of fossil fuels; mitigating the deadly effects of catastrophic global climate change. To safeguard and preserve our one and only life-support-system—Earth's Biosphere; in a habitable condition for all humans, animal and plant species to continue living. That the air we breathe, the water we drink remains clean and healthy; not poisoned by the toxic wastes we generate. Deploying drones to serve humanity. To generate clean energy; to preserve clean air; clean water; and a healthy planet Earth for future generations! That humans doesn't follow the dinosaurs—into extinction! Yeah, drones! Drones to the rescue of humanity! Drones to save mankind from this self-inflicted ecological suicide!

The harnessing of renewable “green” energy from the mass movement of naturally occurring fluid elements comprising wind; the capture and transformation of this kinetic energy into useful mechanical energy by means of specialized vehicles and a bagged power generation system configured for producing electricity comprising: wind powered generators. In particular wind energy comprising: high altitude wind energy; the Jet Stream. The harnessing and transformation of the fluid's kinetic energy into useful mechanical energy by means of tethers attached to the Hybrid Aerial Vehicles (HAV-400); production of stored potential energy; and electricity by means of generators. Specialized airborne Flying Energy Generators (FEGs) comprising HAV-400 configured to harness the kinetic energy of high altitude winds for doing useful work. A method, system, equipment, apparatus, techniques and a drone ecosystem configured with vertical scalability and a quantum leap in the generation of renewable green energy: electricity, in comparison with existing systems at a minimized environmental and aesthetic cost.

### BACKGROUND OF THE INVENTIONS

Present methods of harnessing wind energy by means of: kites, wind mills, wind turbines, kytoons, airfoils, etc.; use of sails on boat, ship or sledge for traction is known; as is the capture of water energy by means of: water mills, water wheels, turbines; balloons mounted on the sea-bed, floatation based devices, etc.; in converting the kinetic energy of wind into mechanical energy to do useful work: mills to

grind flour, pump water, etc. including aero-electric power and hydro-electric power generation. However, some devices like: wind mills, wind turbines may be deficient and self-limiting due to (i) the minimized surface area for capture of the kinetic energy of the fluid medium as evidenced by the limited size and number of turbine blades, rotors, propellers, spokes; sails, etc. that may be affixed to an apparatus; (ii) the extremely short, momentary, contact time between the drive surface and the moving fluid medium providing the kinetic energy lasting a few seconds; and (iii) harnessing the kinetic energy in an ad-hoc randomized manner. Harnessing the energies of mother-nature in quantities huge enough for global consumption by means of utility scale generation plants/or farms; may require different approaches and solutions from conventional methods, systems and apparatus presently available. In particular high altitude wind energy, the Roaring 40's, the Furious 50's, the Shrieking/or Screaming 60's, the Jet Stream (exceeds 92 km/h; up to 398 km/h).

The low altitude sector (800 m to 1 km) of wind energy typically harnessed by wind turbines mounted on fixed towers comprises about 2% of the total global wind power. Whereas 98% of the global wind energy lies out of reach at a height of above 800 meters; and may be extracted by means of airborne wind energy systems operating above this altitude.

Present invention discloses methods of using tethered, Hybrid Aerial Vehicles (HAV-400) which may be transformed from their original airplane shaped bodies into different shapes as configured such as: puffed up and enlarged; Delta-shape; V-shape; etc. Thus maximizing its lifting efficiency; in effect being transformed into an airborne sky-crane; a wind-driven-sky-lifting vehicle capable of harnessing kinetic energy 11 of wind 10 movement; transforming it into green electricity directly; or indirectly when used in tandem with stored potential energy systems for generating potential energies which may in turn be converted into electricity later, as and when needed; such as 100% artificial green hydro-electricity. HAV-400 may also be used as a prime-mover to lift arrays of wind turbines/or carrier-apparatus mounted with wind turbines into high altitude in order to harness much more powerful wind energy. Configured as a glider drone, the engine of HAV-400 wind crane may be powered off at height; utilizing the surrounding wind power to generate aerodynamic lift; to power its internal system of ram air turbines (RAT) 71aa; 71ab; 71ac; for running onboard systems and equipment.

The forward moving force/or kinetic energy 11 of the wind 10 moving over the aerodynamically shaped surfaces of the HAV-400 creates a huge aerodynamic force lifting the vehicle vertically upwards at an angular inclination relative to the tether line 50aa cum reel system 52aa. This upward lifting force pulling on the attached tether line (kinetic energy 11) exerted a tensional force which turned the tether spool 52aa/or line reel drums 52aa. This rotational movement (mechanical energy 12) is transmitted via a transmission gear-box 53ag; and used to power a driven appliance 54ag comprising: a pump/or, compressor to produce potential energy 13/or, a generator to produce electrical energy 14. A multitude of such HAVs-400 and tethers-lines 50ag (drive unit 51ag) comprising thousands/or hundreds of thousands in number may be timed and arranged to take turns to drive the generators 54ag (driven unit 55ag) to produce Gwh/year or Twh/year of electricity 14. The HAV-400 and attached tether-line 50ag comprises drive unit 51ag. The revolving bobbin/or tether spool 52ag/or line-reel-drum 52ag; gear box 53ag cum generator 54ag comprises the driven unit

55ag. A winding motor 49ag may be used to operate the reel-drum 52ag to retract back the tether line 50ag and HAV-400. Towards the end of the power run/or end-of-run (EOR) point 288aa, the HAV-400 may be depowered by changing its aerodynamic wings profile into neutral lift; and then into negative lift; retracted, retrieved and pulled back (free load) to start-of-run (SOR) point 16aa; “ground zero”; where it may operably change its aerodynamic body profile into positive lift; and redeployed.

### SUMMARY

Present invention discloses a method, system, equipment, apparatus, techniques and drone ecosystem for generating electrical power, comprising of: a shape-morphing glider-drones HAV-400, a mobile navigable vehicle body pulling a tether (drive unit 51ag) attached to an electricity generation module (driven unit 55ag). Such a dynamic method of power generation utilizes a vehicle generating a tremendous amount of aerodynamic lift; thus moving the vehicle vertically upwards at an angle relative to the direction of flow of the fluid medium; with the tensile force created in the tether line 50ag powering the generation module to produce electricity for the duration of its entire upward movement. In the wind-borne form this apparatus may be configured as a hybrid Unmanned Aerial Vehicle (UAV-400)/or Hybrid Aerial Vehicle (HAV-400). Equipment, apparatus and an ecosystem for operating the aerial drone may be mounted on and borne by the vehicle body, including: flight control surfaces, tether lines, bridle lines, control lines 46, retract lines, winches, motorized turbo-fans, propellers, side-thrusters, batteries, engines, compressed air-tanks, helium tanks, fuel tanks, balloons, ram-air-turbines, etc. Enabling capabilities includes providing airborne work-stations 44aa for station hopping, thus extending the range and power-run of the drive units 51. The airborne platform may comprise of highly specialized supporting systems such as the Unmanned Aircraft System (UAS) infrastructure for aerial drones. Said vehicles being remotely navigated, controlled and operated by human navigators by means of transmission wire-lines embedded into the tether lines 50ag; or remotely by means of radio frequency (RF) and sonar signals.

Disclosed herein is a motion-centric method; and dynamic system of generating power by means of specially configured motion based vehicles/motile apparatus; navigable vehicles traversing a fluid medium on a relatively linear trajectory or path of travel (from SOR point 16aa to EOR point 288aa); said multitude of fluid propelled navigable vehicles travelling in proximity may be remotely manipulated to avoid collision/or to maintain a journey free from interference from like vehicles. Said navigational means comprises ground based and onboard radar and sonar transmitters, receivers, sensors and cameras linked to a computerized Advanced Warning System for proximity warning to prevent collision. Including propulsion engines 408; thrusters 70ae; control surfaces comprising: wings 404; stabilizers 405; tail controls 406; emergency equipment comprising solid propellant discharge nozzles 242ar; compressed air nozzles 242aa.

Computerized self-navigation capability enabled by means of drone technologies along an assigned trajectory may also be incorporated into the guidance system of the drones. The main thrust of present invention comprises of: a HAV-400; essential components comprising a: shape morphing vehicular body; tether; surface based energy generation system. A tether line for transmitting the motive forces/ or kinetic energy of the fluid propelled vehicle to a ground

and/or surface based electricity generation system. The motion-centric vehicle moving vertically at a diagonal angle; extracting their energies as they traveled from the SOR point 16aa to the EOR point 288aa; generating power continuously and consistently for the duration of the whole upward journey. The full force of the fluid’s aerodynamic lift may be imparted onto the widespread wings of the HAV-400. The desired amount of drag force may be set into the generator system—manually by hand; computerized auto controls or varied accordingly to maintain optimal operating conditions. Shape morphing wings attached to the vehicle bodies may be deployed and retracted while traversing in said fluid medium as and when desired/or commanded; as the vehicle navigated along a designated trajectory. The vehicle body and wings profile may be altered, to shrink and extend in shape; size; surface area; to provide changes in its aerodynamic configuration. Such that the HAV-400 changes its lifting capabilities comprising: positive lift (vehicle moves upward); neutral lift (vehicle stays at stationary height); and negative lift (vehicle moves downward).

### BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the present invention will now be described with reference to the accompanying drawings wherein:—

FIG. 1A shows details of a fully deployed HAV-400.

FIG. 1B shows details of the cross-sectional side view 1B-1B of FIG. 1A;

FIG. 1C shows details of FIG. 1B with the drone’s body at maximum inflation and generation of maximum aerodynamic lift.

FIG. 1D shows details of the composition, components and body structure of HAV-400.

FIG. 1E shows details of a compressed air generation and helium gas recycling system.

FIG. 1F shows details of the frontal view (fore) of FIG. 1A; and the internal construction and structural components of HAV-400’s body at maximum inflation or lift.

FIG. 1G shows details of FIG. 1F with HAV-400’s body profile at neutral lift;

while FIG. 1H shows details of the body profile at negative lift.

FIG. 1I shows details of the original body of HAV-400M.

FIG. 1J shows details of a fully morphed variant HAV-400M with extended wind engaging bag.

FIG. 1K shows details of a plan view of the shifting body contours of HAV-400.

FIG. 1L shows details of the deployment of wind engaging bag extended at the periphery of HAV-400.

FIG. 1M shows details of a plurality of UATV-80aa flexibly attached to HAV-400.

FIG. 1N shows details of an air-rib 277aa and solid rib-cage structure.

FIG. 1O shows details of attachment between plates 416 and metal ribs.

FIG. 2A and FIG. 2B shows details of the use of a HAV-400 in supporting role.

FIG. 2C shows details of a plurality of HAV-400 lifting an aerial work station enabling servicing and tether lines swapping of HAV-100aa.

FIG. 2D to FIG. 2E shows details of an airborne docking sub-system 430.

FIG. 2F to FIG. 2H shows details of the sequential deployment phases of a HAV-100aa upon release from docking sub-system 430 of work station 44ab.

FIG. 2I shows details of the forces generated on a tethered HAV-400.

FIG. 3A to FIG. 3B shows details of sub-system 440 and sequential phases and locations of a HAV-400 used with driven unit 55ag to produce electricity.

FIG. 3C shows details of sub-system 450 comprising a stored potential energy system for producing electricity on demand. FIG. 3D shows details of sub-system 460 comprising of a pumped hydro-electricity generation system.

FIG. 4A shows details of a sub-system 470 comprising a line of wind turbines airlifted by HAV-400. FIG. 4B shows details of sub-system 480 comprising an array of wind turbines built into a framework, carried aloft.

FIG. 4C shows details of the sectional side view of a counter rotating double sided turbine generator. FIG. 4D shows a sectional view 4D-4D of the generator.

FIG. 4E shows details of the side view; while FIG. 4F shows the sectional plan view 4F-4F of a vertically oriented counter rotating double sided turbine discs generator.

FIG. 4G shows details of a quad-bladed turbine generator of FIG. 4C; the turbine blades embedded with generating elements.

FIG. 4H shows details of a counter-rotating double sided wind turbine generator; the turbine blades embedded with generating elements.

FIG. 4I shows details of a counter-rotating vertical shaft wind turbine generator.

FIG. 5A shows details of a plan view; while FIG. 5B shows the sectional side view 5B-5B of a multi-tiered counter-rotating turbine generator.

FIG. 5C shows details of an airborne turbine generator lifted vertically by a HAV-400; while FIG. 5D shows a turbine generator lifted in an inclined position.

FIG. 5E shows details of the front view of a three bladed wind turbine generator; while FIG. 5F shows the front view of a six bladed turbine generator. FIG. 5G shows the front view of a multi-bladed turbine generator.

FIG. 5H shows details of the sectional side view 5H-5H of FIG. 5G; while FIG. 5I shows the sectional side view 5I-5I of a double layered arrangement (side by side; or over-under configuration) of the twin turbine generator of FIG. 5E; FIG. 5F and FIG. 5H.

FIG. 5J shows details of the sectional side view of a double layered arrangement (side by side; or over-under configuration) of the twin turbine generator of FIG. 5A and FIG. 5B.

FIG. 5K shows details of a HAV-400 wind-lifter carrying aloft a plurality of wind turbines 471; 500; 500a. FIG. 5L shows a rack container for keeping wind turbines.

FIG. 5M shows details of a HAV-400 wind-lifter carrying aloft an airborne wind turbine 500a in an inclined position. Including a seaborne ecosystem for processing the renewable energies harvested by means of floating electrolyzer plants.

FIG. 6A shows details of an airborne wind energy harvesting system 510a by means of windbags. FIG. 6B and FIG. 6C shows more detailed illustration of the main components. FIG. 6D and FIG. 6E shows the fine details of FIG. 6B and FIG. 6C. FIG. 6F shows an optional arrangement for avoiding line interference.

FIG. 6G shows a high altitude ground station used with an airborne station.

FIG. 6H shows details of a locking clamp mechanism for securing guide lines. FIG. 6I shows details of the side view; while FIG. 6J shows the front view of robotic limbs holding guide lines securely.

FIG. 6K shows details of a windbag outfitted with accessories. FIG. 6L shows a RF activated pressure control apparatus; and air nozzle. FIG. 6M shows a telescopic cover and string 33aa. FIG. 6N shows details of the rotational sequence in which a plurality of generators 55aa may be positioned relative to the power run phase; retract phase; standby phase.

FIG. 6O shows details of a seaborne water energy harvesting system 510u enabled by means of water-bags.

FIG. 6P shows details of an improved system 76av in power run comprising multiple windbags for harvesting wind and/or water energy; guided by a navigation unit HAV-400. A water-bags system 222av for harvesting water energy. FIG. 6Q shows the retraction phase of the system.

FIG. 6R shows details of adaptation of underwater sea-mounts 555 for anchoring cables for surface vessels harnessing and processing renewable energies. FIG. 6S shows details of securing an anchoring beam; and a plug in caverns.

FIG. 6T to FIG. 6W shows details of a funnel shaped undersea structure to converge sea water to power water turbines. FIG. 6X shows details of a turbines tunnel.

FIG. 6Y shows details of a plurality of submerged water turbines.

FIG. 7A shows details of a plurality of glider drones HAV-400 to increase tensile force acting on a driven unit.

FIG. 7B shows details of system 600; in which the tensile force from a plurality of drive units may be transmitted back to a centralized power generation plant.

FIG. 7C shows details of line reel drum 582 integrated with the gearbox 583; clutch 587; and retract motor 589.

FIG. 7D shows details of system 600; with a plurality of discs generators 590d. FIG. 7E shows details of said dual discs generator. FIG. 7F shows details of two inter-connected line reel drums.

FIG. 7G shows details of system 600; with new extension apparatus to transmit the harnessed energies to the generator 590h. FIG. 7H shows details of counter rotating generator 590h.

FIG. 7I shows details of improving the efficiency of a combined cycle generator.

FIG. 8A shows details of using water-bags to divert and converge ocean current into a seaborne hydro power generation tunnel. FIG. 8B shows details of a parallel windbags system to concentrate wind current into an aero power generation system.

FIG. 8C shows details of a flying carpet system comprising strips of solar fabrics mounted on light weight aero-foams; carried by glider drones HAV-400. FIG. 8D shows the use of such apparatus on water surface as solar energy collectors.

#### DETAILED DESCRIPTION OF THE INVENTIONS

The structural configuration, concept, method and system of providing an unmanned morphing HAV-400 for harnessing and extracting the energies contained in a moving air current (wind) for the generation of electricity; is herein disclosed. Transforming its kinetic energy into mechanical and then electrical energy by means of a tether.

The working principal of a HAV-400 lies in maximizing generation of aerodynamic lift. The airborne system may comprise of: customized aerial drone HAV-400 and tether 50ag (Drive Unit 51ag); Generation Modules housing the tethers-line reels 52ag, gear-box 53ag, generators 54ag (Driven Unit 55ag); computerized ground control systems, control links; navigators; supporting systems, equipment;

radar system, GPS; Inertial Navigation System; parking aprons, control and command centre; Unmanned Aerial Tow Vehicles (UATV) **80aa**; power collection grid; etc. Driven Unit **55aa** may be integrated with other mechanical components such as air compressors; water pumps. The drive unit may be used to lift or carry heavy loads such as containers filled with fluid (water); solid blocks of concrete; metal; rocks; earth; timber; etc.

Glider drones HAV-**400** may be used to lift a variety of items into high altitude to harvest wind energy such as: wind turbines **490h**; **490d**; **477v** **500a**; **500b**; **500c**; **500d**; airborne work stations; air-bridges **429p**; **429r**; control a multitude of drive units **30aa** to generate power; drive generators **584**; **590d**; **590h**; etc. The combination of: a distributed system for extraction of energies comprising: high altitude wind current and deep sea ocean current; a tensile force transmission system to; a utility scale centralized power generation plant **585**. Airborne wind energy harvesting system **510a** using windbags; seaborne energy harvesting system **510u** using water-bags.

FIG. 1A illustrates a deployed glider-drone HAV-**400** with its body parts fully extended to generate aerodynamic lift; connected to a load, driven unit **55ag** by means of tether **50ag**; while FIG. 1B illustrates the cross-sectional length-wise side view 1B-1B of FIG. 1A with an inflated body profile. FIG. 1C illustrates further enlargement and puffing-up of the body of FIG. 1B to attain maximum inflation, for generating the maximum lift configuration that the drone had been designed to produce. Also illustrated are: wind inlet port **401**; hollow cavity **402**; exit port **403**; control surfaces comprising: wings **404a**, **404b**; stabilizers **405a**, **405b**, **405c**, **405d**, **405e**; tail controls **406a**, **406b**, **406c**; wheels **407a**, **407b**, **407c**; engine **408**; cooling fins **418a**. Since the HAV-**400** operates as a tethered glider-drone 99% of the time; engine **408** may not be required at height. It may be used during take-off and for emergency propulsion purposes only.

Airplane shaped, HAV-**400** may comprise of a flying-wings body design wherein, the whole body of the vehicle may take the form of, and be shaped like the profile of an aircraft's wings; configured with standard conventional flight control surfaces comprising wings **404**; side stabilizers **405**; main vertical stabilizer **406a**; horizontal stabilizers **406b**; **406c**; rudder; slats; flaps; ailerons; elevators. Alike typical wings of an airplane; ailerons and flaps present in wings **404**; may be manipulated to minimize or maximize aerodynamic lift generation, flight control and loading capacity of the drone. HAV-**400** looks much like the shape of a manta-ray, but with the capability of a puffer fish to can suck in air, puffing up its stomach, distending its flat, thin discus-like body into an enlarged balloon several times its original body size. In HAV-**400** this feature is applied selectively to inflate and deflate specific part(s) of the drone's body as and when required; to manipulate generation of aerodynamic lift to ascend, stay aloft, descend. The motivation for adapting the flying-wings body configuration is for the purpose of: maximizing generation of aerodynamic lift from the harnessing of high altitude wind energy; and employing the morphing body profile to do useful work for mankind. Not for the purpose of high speed flight, fuel efficiency, cost savings, or stealth capability.

While tether line **50ag** bore the main load for doing useful work; HAV-**400** may also be anchored and manipulated by means of control line **46aa** or retract line **33aa**. At the drive end, tether **50ag** may be connected to the three bridle lines **21aa**, **21ab**, **21ac** joined together at point **410**. The three bridle lines may in turn be flexibly connected to HAV-**400** at

points **409a**, **409b**, **409c**; on the drone's body, linked to concealed winches **59aa**, **59ab**, **59ac**; sliding in and out via points **409**; during adjustment of lines and angular inclination of the drone's body relative to wind flow. At the driven end tether **50ag** may be connected to the load, driven unit **55ag** for producing electricity. Flight control surfaces **404**, **405**, **406** may be manipulated and used to vary HAV-**400**'s load carrying capacities; maximum lift (ascend), neutral lift (stay in position, hover) negative lift (descend). The leading edge's angle of attack (of the drone's body) may be adjusted automatically by varying the length of the **3** bridle lines **21aa**; **21ab**; **21ac**; by means of concealed winches **59aa**; **59ab**; **59ac**; in tandem with variability in the generation of aerodynamic lift produced by the variable shape and form of the drone's body.

The HAVs-**400** may be configured with one bridle line **21aa** attached to the bow section (fore) at point **409a**; line **21ab** to starboard side at point **409b**; and line **21ac** to port side at point **409c**; joining together with tether line **50aa** at point **410**. The lengths of the bridle lines **21** may be adjusted by winches **59aa**; **59ab**; **59ac**; to tilt and vary the vehicle body's position and angular inclination relative to the wind direction; thus optimizing the HAV-**400** body's angle of attack. This provide a secondary means of adjustment; maximizing; or minimizing the HAV-**400**'s aerodynamic load lifting capacities; apart from the primary generation of aerodynamic lift by means of the morphing body and changes in the wing's angle of attack.

Thus the directional, flight controls and load-lifting adjustments of HAVs-**400** may be effected by means of: (a) Variations in vehicle shape (morphing) by means of pneumatic system for inflating/or deflating windbags **420** system constituting the airframe; said windbags **420** comprising: air-pillars **420a**; air-pouches **420b**; air-pads **420c**; air-packets **420d**; air-cells **420e**; air-ribs **277aa**, **277ab**. (b) Variations in the angles and length of the three bridle lines by means of winches **59aa**; changing the position of the drone's body; and thus the main body's leading edge's angle of attack. (c) Variations of conventional wings and tail mounted flight control surfaces **404**, **405**, **406**. Sensors **411** on the drone's body interacts instantly with onboard and ground computer systems regarding its vital operating parameters and ambient conditions; adjusting and correcting its flight parameters accordingly.

FIG. 1D illustrates the preferred components used in constructing HAV-**400**. Solid structural framework **412** may comprise of: round pipes **412a**; rectangular pipes **412b**; square pipes **412c**; girders; C-channels; V-channels; etc. Materials making up this body framework structure may comprise of: metallic; composites; carbon-nano-fibers; fiber glass; ceramics; Kevlar; carbon fiber reinforced plastics; glass fiber reinforced plastics; quartz fiber reinforced plastics; aluminum glass fiber laminates; glass laminate aluminum reinforced epoxy (GLARE). This structural framework is overlaid by the air-frame comprising layers of flaccid shaped air-bags **420** comprising air-pouches **420b**; air-pads **420c**; air-hoses **413a**, air-tubes **413b**; covered by an external layer of skin **415** bound by straps **415a** made of lifting harness materials; Dyneema; Spectra; Kevlar; etc. Solar fabrics **415b** may be embedded into the fabric materials of the uppermost layer of skin **415** to harness solar energy in flight. Optionally the skin **415** may be coated with a layer of reflective material to reflect back the sun's rays outward into space; creating an albedo effect. Deployed in large numbers, HAVs-**400** may also provide a form of sun-shade to the surface below; reducing ambient temperature and the intensity of heat waves. This may be similar in effect to proposed

geo-engineering initiatives of spraying a layer of airborne chemicals/surfactants on the ocean's surface to reflect sunlight back into space to mitigate the severity of global warming cum global climate change.

Optionally, the external surface of the vehicle body may comprise of large pieces of over-lapping scale-like-plates **416**; an exo-skeleton providing strength and support. Such external plates may be inter-connected by a layer of pliable, durable membrane like material; and in turn mounted on an inner layer of fabric skin; replicating the reptilian skin in design; or flexibly connected to a framework and network structure of pliable ribs **446** by mean of sliding rings **447** (Refer FIG. 10). The plates may be made of: metals; ceramics; composites; carbon fibers; plastics; thermoplastics, reinforced fabrics, etc. While the internals of the body comprising of: windbags, airbags, air-ribs, fabric; etc. may be arranged wherein a plurality of layers configured on top of one another may be inflated or deflated individually or in groups upon requirement. Such that variations in height or thickness of the body as desired, may be achieved by means of inflating and deflating designated pieces or groups of airbags **420**; or layers of such airbags **420** stacked on top of each other. Minute adjustments to the airframe may be made by means of small sized air-packets **420d**; air-cells **420e**. While adjustment of air pressure may be used to balance the turgidity between air-ribs **277aa** and **277ab** in order to optimize external shape and aerodynamic lift generation of HAV-400. (Refer FIG. 1K)

The structural configuration of HAV-400 may comprise of two main components: (1) a solid skeletal body framework **412**; covered by an external (2) airframe consisting of airbags **420** system which may be selectively inflated or deflated by means of pneumatic control and distribution system **421**; with commands from computerized algorithms, logic and programs. The structural configuration of windbags/or airbags system **420** comprises a plurality of variably shaped: air-pillars **420a**; air-pouches **420b**; air-pads **420c**; air-packets **420d**; air-cells **420e**; air-ribs **277aa**, **277ab**; including: air-hoses **413a**, air-tubes **413b**; 2-ways switching valves **414**, 3-ways switching valves **414**. The term airframe in present invention differs slightly from the normal meaning of "airframe" used to describe aircrafts; as it comprises 100% air inflated windbags **420** filled with compressed air/or helium gas; providing turgidity to the drone's body; giving HAV-400 its external shape, contour, morphology. Such that inflation and deflation of strategically positioned air-bags **420** changes the shape of the drone's body enhancing its aerodynamic properties; enabling it to attain neutral, power-up, depowering capabilities; allowing useful work to be done safely. Solid skeletal body framework **412** may comprise about 20% of the total drone body's component.

A ram-air-turbine (RAT) **71** is central to the working mechanisms of HAV-400; as a huge amount of compressed air is required for inflating the airframe of the vehicle comprising air-bags system **420** consisting of a variety of shaped: air-pillars **420a**; air-pouches **420b**; air-pads **420c**; air-packets **420d**; air-cells **420e**; air-ribs **277aa**, **277ab**; including: air-hoses **413a**, air-tubes **413b**; switching valves **414a** and **414b** activated by means of computerized signals. Three ram-air-turbines (RAT) **71aa**, **71ab**, **71ac** may be configured in series into the center of the drone's body for redundancy. An oval shaped hollow cavity **402** ran the whole length of the drone's body, from the fore (bow) through the aft (stern). High speed wind enters via fore mounted wind-intake port **401** driving ram-air-turbines RAT-**71aa**; **71ab**; **71ac** mounted inside cavity **402**; expended air exiting via aft mounted port **403**. RAT-**71aa**; **71ab** may be used to produce

compressed air; while **71ac** may be used to generate electricity for onboard use. Compressed air produced by RAT-**71aa** driven compressor **417** may be cooled by means of air cooler **418**; stored in cylinders **419**; used to inflate the air-frame components as and when needed; and released into the atmosphere upon deflation of the air-bags **420**. Optionally, HAV-400 may use lighter-than-air helium gas to inflate its air-frame.

Present invention discloses the use of high altitude wind current to: (1) Generate an aerodynamically shaped body profile (HAV-400) by means of compressed air for inflating a multitude of windbags/or airbags **420**. (2) Creating aerodynamic lift on said body (HAV-400) of (1) above; to do useful and productive work for mankind; in a self-sustaining airborne system without the need for external input of energy; except for the initial lift to become airborne. Minor repairs might be carried out on the flying airborne platform **44ab**; which double as a refueling station store, parking lot, crew change, etc. The drone is configured to stay airborne for extended periods of time until major maintenance required for it to land.

FIG. 1E illustrates a compressed air generation sub-system **422a** and/or a helium gas recycle sub-system **422b**. In sub-system **422a**, compressed air generated by means of RAT-**71aa**; **71ab** driven compressor **417** may be cooled down by an air-fin cooler **418**; stored in cylinders **419**; controllably released by means of a computerized pneumatic control and distribution system **421**; to selectively inflate the air-frame comprising specific airbags **420**; by means of a network of air-hoses **413a**, air-tubes **413b**, two-ways switching valves **414a** and three-ways switching valves **414b** activated by means of computerized signals from system **421**. Valves **414** may be operated to inflate airbags **420** with compressed air from tank **419**; and to deflate airbags **420** by venting off into the atmosphere; in a controlled manner as and when required. Cooling fins **418a** of the air-fin cooler **418** may be embedded into the sides of hollow cavity **402**. Optionally, if helium gas is used for inflating airbags **420**, the helium gas recycle sub-system **422b** may be adapted. Due to its rarity, helium gas is not vented off after use, but recycled back to RAT-**71aa** driven compressor **417**; air-fin cooler **418**; containers **419** and reused repeatedly. Air-Driven-Generators (ADG); Air-Driven-Compressors (ADC) comprising Ram-Air-Turbines (RATs) **71aa**; **71ab**; **71ac** may be used to power all systems aboard HAV-400: hydraulic, electrical, pneumatic systems; for operating flight control surfaces; pressurization of the airbags **420** system; directional control air jets **242aa**; engines **70aa**, winches **59aa**, etc. All components and materials used being designed and selected for their superior properties comprising: lightweight; durability; pliability; reliability; superb integrity; fire-resistance; etc.

FIG. 1F illustrates the cross-sectional breath-wise front view (bow) of the HAV-400 of FIG. 1A; and structural components of HAV-400's body at maximum inflation and lift (refer FIG. 1C). A large oval shaped wind inlet port **401** is located at the center-bow of the drone's body; lying atop solid structural components **412**; covered by the external airframe structure **420**; including: wings **404**; main vertical rudder **406a**; topside stabilizers **405a**, **405b**; hull side stabilizers **405c**, **405d**, **405e**; integrated with wheels **407a**, **407b**, **407c**. Also shown are internal construction and components of HAV-400; structural arrangement and architectural configuration of the vehicle's airframe mechanism comprising airbags system **420**. The variety of shaped inflatable fabric airbags **420** system comprising: air-pillars **420a**; air-pouches **420b**; air-pads **420c**; air-packets **420d**;

air-cells **420e**; air-ribs **277aa**, **277ab**. Air-ribs **277aa** may be configured around the circumference of the elliptically shaped HAV-400; while air-ribs **277ab** may be configured to support top deck **423d** and underbelly **423u** surfaces. Air-pillars **420a** are the equivalent of structural beams providing support for the top deck **423d** and underbelly surfaces **423u** of the drone's body; etc. giving it external shape and form. Thus air-pillars **420a** may comprise thicker and much more robust fabrics to withstand much higher pressure required than the air-pouches **420b**; air-pads **420c**; air-packets **420d**; air-cells **420e**; which are the equivalent of body tissues. Air-pouches **420b** comprises large box like cubes in form; while air-pads **420c** comprises square or rectangular pieces of flat mattress/or cushion shaped. Air-packets **420d** forms small adjustment pockets of air; while air-cells **420e** enables minute space filling of gaps and topping up in between the other larger shaped bodies of airbags for a smooth exterior body surface. This is important in establishing a smooth air flow for optimized creation of aerodynamic lift. The air-frame provided by compressed air or helium gas in airbags **420** works in tandem with solid-frame components **412** (refer FIG. 1D) which provides the structural skeletal backbones of the HAV-400.

Internal airbags configured into the top deck **423d** and underbelly **423u** portions of the body may be selectively inflated; or, deflated; their activation varied to change the body shape of the HAV-400; and their aerodynamic lifting capacities as and when required, in tandem with variations in the "angle of attack" of the body's leading edge and the wing's **404** leading edge. Wherein, neutral aerodynamic lift of a vehicle may be used to support the HAV-400's own weight of (e.g. 1 to 10 tons), keeping it airborne in a relatively steady hovering location/position. While generation of positive aerodynamic lift up to maximum lift by the wings and morphed body of the HAV-400 may be used for its ascent; enabling lifting of its designed load from its standard hovering height (e.g. 1 km level) to a greater height (e.g. 10 km level). The required lift may be varied by adjusting the shape of the body and wings profile to suit the load (drag) it is required to lift up and carry.

At high altitude, high speed wind current (e.g. 100 km/h) might be able to create adequate aerodynamic lift to power a tethered drone-glider HAV-400 to lift a heavy load. Such that for a drone with an aerodynamic lift generating surface area comparable in dimension to that of a commercial aircraft (e.g. Boeing, Airbus); a "loaded-positive aerodynamic lift" (e.g. 100 tons) may be achieved by means of balancing the HAV-400's own weight (e.g. 20 ton) plus the added load it is bearing/useful work done (e.g. 80 tons); relative to the required lift coefficient needed to keep the vehicle in a steady location/position. Negative aerodynamic lift (below neutral) generated by the morphing body and wings may be used for rapid descent of HAV-400; enabling retraction of tether lines **50aa** and for the HAV-400 to return from its EOR point (**288aa**) to its SOR point (**16aa**) speedily.

A flying-wings-work-horse, HAV-400 may be used for generation of renewable energies and performing a variety of other heavy lifting tasks. HAV-400 may be used: (a) In a supporting role; in enhancing efficiency of HAV-100s; as a support vehicle (refer FIG. 2A to FIG. 2C) for provision of heavy lifting; enabling work stations **44ab** to stay airborne; (b) Independently by itself as drive unit **51aa** for generation of electricity; and stored potential energy. Three basic types of traction lifts may be performed by HAV-400 comprising: (1) batch lifting of static load comprising a heavy body e.g. blocks of stone; timber logs; etc. from one point to another

point; (2) fixed position static lift e.g. carrying aloft an array of wind turbines to harness high altitude wind energy, and staying at a fixed location for an extended period of time; (3) running lift; in which a continuous force is exerted throughout its journey from SOR point **16aa** to EOR point **288aa**, e.g. running generators; pumps; compressors. HAV-400 may be configured with fixed bodily structure and deployed as such. Optionally, the airplane-shaped-body may be transformed into a variety of configurations comprising: V-shape; Delta-shape; 5-angled; rectangular/or, resembling a full-moon-shaped-kite called the "wau-bulan"; etc.

FIG. 1G illustrates the front view and body profile of HAV-400 in a hovering position, in which the top deck **423d** curvature of the airframe is minimized (while underbelly **423u** remains the same) in comparison with FIG. 1F. The drone is at neutral aerodynamic lift; such that minimum lift generated roughly equals the body weight/or mass of the drone itself (zero load). While FIG. 1H illustrates generation of negative aerodynamic lift wherein the underbelly **423u** curvature of the airframe is increased (while top deck **423d** remains the same) in comparison with FIG. 1F; such that the drone descends from height rapidly towards ground level.

FIG. 1I and FIG. 1J illustrates a variant form comprising a morphing kite-drone HAV-400M; configured with concealed extensions of body-framework comprising: wing frames **424**, bow frame **425**; body length **426**; and a collapsible arrangement of stowed windbag fabrics **30aa**; air-ribs **277aa**, **277ab**; etc. These concealed extendable and retractable solid body frames **424**; **425**; **426**; air-ribs **277aa**; and a plurality of variously shaped airbags **420** hidden within may be deployed thereby transforming, morphing the HAV-400M into an enlarged and elongated body-frame with increased length and breadth. Whereas from wing-tip to wing-tip; from nose to tail; the HAV-400M may be configured to vary from 10 m (normal pre-launch; launching) morphing up to 20 m (after launch; airborne) upon full extension of the HAV-400M's concealed body parts **424c**; **425c**; **426c**. Deployment of concealed fabric materials **30aa** stored lengthwise inside the belly of the main body transforms the drone into a kite shaped wing-suit apparatus/or a kite; kite-drone; kite-glider-drone. Winches **59aa** and embedded lines **23aa**; **66aa** and pulley wheels **68aa** beneath the wing-span pulls the fabric material **30aa** breath-wise, opening up the wing-suit. Inflated air-ribs **277aa** on the periphery of fabric materials **30aa** kept the desired shape in place. Additional bridle lines **21aa** may be used to link fabrics **30aa** to the common joint **410**. The fabric materials **30aa** may be deployed and retracted as required to harness high altitude wind energy. Solar fabrics **415b** may be embedded into bag fabrics **30aa**.

FIG. 1K illustrates the change in the circumference of the body shape of HAV-400 between generation of maximum and minimum aerodynamic lift. Outer contour line **427d** indicates the extended circumference of the drone's body when it is deflated and flaccid as shown in FIG. 1G; such that peripheral located air-ribs **277aa** are fully inflated and extended while top deck located air-ribs **277ab** are deflated and flaccid; giving neutral/or minimum lift. Inner contour line **427i** indicates the shrunken circumference of the drone's body when it is fully inflated and puffed up as shown in FIG. 1C; such that top deck air-ribs **277ab** are fully inflated and extended while peripheral air-ribs **277aa** are deflated and flaccid; creating maximum lift; using minimum body mass.

FIG. 1L illustrates a variant form wherein HAV-400 may incorporate fabric materials **30aa** around the circumference of its body to engage and capture wind. The fabrics **30aa**

may be extended and retracted as required by means of air-ribs **277aa**; embedded lines **23aa**; **66aa**; rings **68aa**; pulley wheels **48aa**. Additional bridled lines **21aa** operated by winch **59aa** may be used to secure the fabrics to joint **410**. Enabling HAV-400 to be flown like a drone glider, kite-drone or windbag **30aa**.

FIG. 1M illustrates use of a plurality of unmanned aerial tow vehicles, UATV-**80aa**; **80ab**; **80ac**; in providing propulsion for elevating a HAV-400 from ground to a suitable altitude for it to generate its own lift before the towing vehicles detaches to return to ground. The three towing vehicles may be flexibly attached to both the port and starboard wing-tips **404** and the main vertical stabilizer **406a**. Optionally, it may be elevated and lifted up by means of another unit of HAV-400 already deployed in high altitude; establish its own aerodynamic lift before being uncoupled/released from the tether line **50ab** of the lifting unit. It may also be elevated by means of "airborne crane" comprising heavy lift helicopters; or towed by a manned aircraft just like a glider till it reaches a suitable altitude to generate its own lift before being released.

FIG. 1N illustrates the use of air-ribs **277aa** concealed beneath the exoskeletal plates **416**; in parts of the body and wings structure which may be configured to be pliable and bendable. Inflation or deflation of the air-ribs **277aa** causes the solid rib-cage **445a**; **445b** structure to extend or retract; pushing up or shrinking the exoskeletal plates **416** covering the wings surface; and may be used to change the cross-section or profile of the wings structure. Such apparatus may be used on the leading edge portion of the wings; or the front leading edge of the main body, from the wind-intake port **401** (bow) running along both sides till the starboard and port side wings **404**.

FIG. 1O illustrates a means of attachment in which the scale like plates **416** of the exoskeleton may be flexibly connected to a framework and network structure of solid ribs **446** by mean of a plurality of sliding rings **447**.

FIG. 2A illustrates the use of HAV-400 in support of the deployment of HAV-100aa. The tether line **50a'** of HAV-100aa may be airlifted to a high elevation by means of a roller wheel **48aa** affixed to tether line **50aa** borne by HAV-400. This allows HAV-100aa to attain higher altitudes speedily to harness more powerful winds to power driven unit **55ag**. Thus HAV-400 displaces the use of tower **286aa** in FIG. 13C of U.S. Pat. Nos. 8,963,362; 9,234,501.

FIG. 2B illustrates the optional use of HAV-400 in support of the deployment of a master HAV-400' leading a multitude of slave windbags **30aa**. Master HAV-400' displaces power consuming UAV-80 in FIG. 5A of U.S. Pat. Nos. 8,963,362; 9,234,501. Such a tandem flight of HAV-400 and HAV-400' requires zero input of external energy and has zero emission as compared to using UAV-80 as previously disclosed. Other prior art disclosures such as connecting windbag **30aa** to retract line **33** at point **32** may also be used. Control line **46aa** or retract line **33aa** may be used to retract back the whole drive unit **51** comprising HAV-400' and tether line **50a''**.

FIG. 2C illustrates the airborne version of station-hopping by means of airborne work-station **44ab**; enabling the HAV-100aa to fly from one station to another without returning to base (please refer waterborne version of station-hopping: FIG. 2A; FIG. 13D of U.S. Pat. Nos. 8,963,362; 9,234,501). Wherein HAV-400 substitutes and displaces the use of HAV-45 in system **44**. As such HAV-400 enabled system **44ab** may also be used to support operation of flying airbags **30aa** and HAV-100aa to generate renewable energy. A plurality of HAV-400s may be used in lifting a work-station

**44ab** (herein also referred to as Station B) into high altitude by means of tether **50aa'**; and staying there for an extended period of time. The system **44ab** may be configured to support a plurality of docking bays **428w**, **428x**, **428y**, **428z**, under air-bridge **429**. Optionally, a docking bay **428** may be borne by tether **50aa'** from a single unit of HAV-400.

A unit of HAV-100aa is shown attached to a docking bay **428w** mounted beneath air-bridge **429** of Station B, **44ab**; and another unit HAV-100ab anchored to two docking bays **428x**; **428y**. Air-bridge **429** may be constructed of rigid, solid structures comprising reinforced fiberglass; glass-reinforced plastics, carbon-fibers; composites; etc. The depleted (in run length) tether **50aa** attached to HAV-100aa (originating from upwind Station A, **44aa**) may be changed over to a fresh (full length) tether **50ab** (originating from Station B, **44ab**) enabling continued operation of HAV-100aa to Station C, **44ac**; without being retracted back to Station A, **44aa**. Airborne checking, servicing, refueling and minor maintenance may also be carried out prior to taking off for Station C. Fresh tethers **50ab** attached to ground based driven units **55ab** may be hoisted from grade up to Station B while depleted tethers **50aa** may be lowered to ground level; and retracted to Station A by means of a dedicated HAV-400; or ground based facilities. Such capabilities enhances flexibility, efficiency and productivity of the renewable power generation plant.

FIG. 2D to FIG. 2E illustrates an anchoring sub-system **430** enabling the link-up, hook-up and docking of a depowered HAV-100aa to a docking bay **428w** mounted beneath Station B. Guidance systems comprising homing signals transmitters **431t**; receivers **431r**; may be used to bring the two bodies into proximity. The depowered HAV-100aa traversing underneath bay **428w** may be brought into alignment by means of its tether **50aa** and motorized self-propulsion mechanisms **70ad**, **70ae**. A flexible U-shaped bracket **432** and suction cups **433a** may be mounted on the belly-side of bay **428w**. A grappling hook **435** attached to line **436** held in a concealed spring loaded self-restraining reel **437**; and suction pads **433b** may be installed on the body **99aa** of HAV-100aa. In proximity, raised hook **435** attached to line **436** on HAV-100aa hitches up with flexible U-shaped bracket **432** which swung backward; bringing the body **99aa** of HAV-100aa closer to the belly of bay **428w**; with the suction pads **433a** and suction cups **433b** attaching themselves together. Suction cups **433a** may also be configured with flexible holders **434** inlaid with vacuuming tubes connected to a vacuum system; and water spray nozzles for enhancing the suction effects between the suction cups **433a** and suction pads **433b**. Other anchoring mechanisms may then be brought into effect such as pneumatic clamps equipped with locking pins; locking arms; locking bars, etc. to grip and immobilize the HAV-100aa.

FIG. 2F to FIG. 2H illustrates the sequential phases of an aerial take off by HAV-100aa from docking bay **427w**. Upon release from the anchoring sub-system **430** of FIG. 2D to FIG. 2E; HAV-100aa detaches and drops downward, slipping away from Station B (blown by the upstream wind) before powering up for its next run segment to Station C; affixed to a full length tether line **50ab** (just changed out at joint **229az**) from driven unit **55ab** located on ground level beneath Station B; the bi-directional winch **59az** is activated to turn the HAV-100 around, wherein the bow and stern exchanges position. Joining point **229az** of the tether **50ab** on the retract lines **33az**; **33ay**; is moved from the bow, point **227az** (FIG. 2F); to midpoint (FIG. 2G); to the stern, point

215az (FIG. 2H). Windbag 30aa may then be deployed propelling the drone downwind of Station B, moving to Station C.

FIG. 2I illustrates the interactive forces generated in a HAV-400. The primary forces comprising the flow of wind current; and the load acting on tether line 50aa; causes generation of resultant forces acting on the drone causing it to move upwards 438 and backwards 439.

FIG. 3A to 3B illustrates a renewable energy generation sub-system 440. HAV-400 may be connected to driven unit 55ag for generating electricity. FIG. 3A illustrates the possible sequence of the various stages of lifting flight; from location L1 marked as Start-Of-Run (SOR) point 16aa; ascending to higher downwind location L2, point 441; then location L3, point 442; until reaching final End-Of-Run (EOR) point, 288aa marked as location L4; prior to depowering; and descending to lower altitudes with slower winds while being retracted back to location L5, point 443; then location L6, point 444; and then finally back to location L1, SOR point 16aa; where it awaited redeployment. FIG. 3B illustrates driven unit 55ag connected to drive unit HAV-400 via tether 50ag for producing electricity by means of tether spool 52ag; gear box 53ag; generator 54ag; and retract motor 49ag. Optionally, system 55ag maybe flexibly connected to air-compressors 55ac; or pumps 55ap; etc.

FIG. 3C illustrates an aero-electric generation plant and sub-system 450. HAV-400 is shown connected to driven unit 55ac comprising line reel drum 52ac; gear box 53ac; air compressor 54ac; and retract motor 49ac; for producing highly pressured compressed air; which may be routed via pipes 452 for storage in spherical tanks 453a; or underground storage facilities 453b (not shown). The stored potential energy in compressed air 451 may be used to run air turbine 454 driven generator 455 to generate electricity 456 on demand; which may be routed to consumers via cables 457 and transmission towers 458. Optionally it may be used to do other useful work on demand. It may also be used together with impact induced energy conversion systems.

FIG. 3D illustrates a pumped hydro-power generation plant and sub-system 460. HAV-400 may be connected to a driven unit 55ap comprising line reel drum 52ap; gear box 53ap; water pump 54ap; used with a stored potential energy system to produce hydro-electricity on demand. Water 461 may be moved by pump 54ap from reservoir 462 at grade to a plurality of elevated reservoirs 463 located at height. Potential energy of stored water 461 from elevated tanks 463 may be used to run water turbine 464 driven generators 465 to produce electricity 456 on demand. For FIG. 3C to 3D instead of using HAV-400, the drive units may be substituted by HAV-100aa. Optionally, instead of directly using HAV-400 to run compressor 54ac or pump 54ap; power produced by drone HAV-400 and generator 55ag in FIGS. 3A and 3B may be used to run the motors powering compressors 54ac of FIG. 3C; or, pumps 54ap of FIG. 3D.

FIG. 4A illustrates a heavy load lifting sub-system 470 for air-lift of a plurality of wind-turbines 471 to harness high altitude wind energy. Wind-lifter HAV-400 carries aloft a linear array comprising a multitude of wind turbines 471 by means of tether 50at for generating electricity. High altitude wind acting on turbine blades 472 mounted on shaft 475 running through turbine housing 473 embedded with stator coils 474 drives horizontal shaft 475 which rotates rotor coils 476 to produce electricity 456, as is known in any wind turbine generators. Vertical shaft wind turbines 477 may also

be airlifted. Electricity 456 generated may be transmitted by means of cables 478 embedded into load tether 50at; or, control line 46aa.

FIG. 4B illustrates a variant sub-system 480 wherein an array of wind turbines 471; of various sizes mounted in a framework or carrier-apparatus 480 may be carried aloft at height by means of tether 50at to harness high altitude wind energy. A plurality of such arrays 480 of wind turbines 471 may be lifted into high altitude to harness high altitude wind energy. Carrier apparatus 480 may comprise of an internal lattice work of square shaped supporting struts 479 and diagonally inclined supporting struts 481; enabling mounting of turbine housing 473. HAV-400 may be kept in location by means of control lines 46aa and ground based system comprising line reel 52aa and winding motor 49aa. A plurality of bridle lines 21aa may be used to connect the tether 50at with carrier-apparatus 480 at point 410. Optionally, a pulley-roller apparatus 482 installed at point 410 may be used to lift or lower the tether line 50at and array of turbines 471 up or down without altering the height of the HAV-400. Such that line 50at may be looped through apparatus 482; one end bearing the load of wind-turbines with the other end connected to a ground line reel system used for control line 46aa comprising line reel 52aa; winding motor 49aa. Fixed or adjustable wind vanes 483 may be used to provide proper alignment of apparatus 480 relative to wind flow; ensuring effectiveness, efficiency and productivity of the system.

FIG. 4C illustrates the cross-sectional side view; FIG. 4D illustrates the cross-sectional view of the motor of FIG. 4C; a counter-rotating airborne wind-turbine-generator system AWTG-490h configured with dual rings of rotor coils and rotor magnets; turning the shaft 475 (and rotor magnet 476h); and yoke 484 (and rotor wire coil 474h) in two opposite directions of rotation. Such a twin rotors concept differs in structural configuration from a standard turbine-generator setup comprising: a stator wire coil 474 and a rotor magnet 476; or conversely (a stator magnet and a rotor wire coil); with single or dual turbines 472 turning the shaft 475 in a single direction of rotation as illustrated in FIG. 4A and FIG. 4B. To this end wind energy harnessed by means of the dual front and rear (fore and aft) mounted turbines may be used to produce counter-rotational movements in both rings of the rotor coils. Such that both rings of rotors comprising: wire coil 474h and magnet 476h are rotating; but in opposite directions to each other; individually connected to and powered by its own dedicated wind-turbine propulsion sub-unit 472f and 472a. Fore turbine 472f may be connected directly by means of shaft 475h to the centrally mounted electro-magnet 476h. Aft mounted turbine 472a may be directly connected to the shell mounted wire coil 474h (surrounding magnet 476h) by means of a yoke 484 connected to hub 485. The generator 473 may be protected by external body cover 473h. A variable electrical (or magnetic flux) controller 466 may be used to vary the supply of current to the electro-magnet 476h of the generator; and thus vary the production of electricity relative to the wind power available at the point in time. If the wire coil 474h rotates clockwise; then the magnet 476h rotates anti-clockwise. Or, vice-versa. Wherein the speed and movement of the generating surfaces of both rotating elements relative to each other may be doubled. Such a double counter-revolving dynamic surfaces configuration of system 490h enables much higher efficiency and productivity as compared to standard airborne wind turbine generators of FIG. 4A and FIG. 4B. And may be used to replace them/or used together with them.

FIG. 4E to FIG. 4F illustrates a variant system with twin "flattened" disc-shaped generating surfaces vertically aligned. FIG. 4E illustrates the side view of a vertically disposed generation system AWTG-490*d*; while FIG. 4F illustrates the cross-sectional plan view of FIG. 4E. Wherein the double counter-rotating discs comprising the wire coil 486 and magnet 487 may be directly connected by means of shafts 475'; 475" and angular transmission gear mechanism 467 to the fore turbine 472*f* and aft turbine 472*a*. If the wind energy harnessed is directly transmitted from the turbines to generator without angular transmission gear mechanism 467, the generating components may be aligned directly facing the wind direction. This incurs undesirable drag forces. To overcome this shortcoming, the counter-rotating discs may be realigned in a streamlined manner relative to the wind flow as shown. The discs may also be oriented horizontally; instead of vertically aligned.

FIG. 4G illustrates a variant system AWTG-490*q* of FIG. 4C and FIG. 4D wherein quadruple turbines comprising two sets of twin counter rotating turbines may be configured in close proximity to each other. The first fore turbine 472*fw* may be connected to the shaft 475*h* to power the generator. While the second fore turbine 472*fx* may be configured to be freely spinning, but turning in a direction opposite to that of front fore turbine 472*fw*. The turbine blades may incorporate/or be embedded with generating elements comprising: wire coils 488 and magnets 489. The first fore turbine blades 472*fw* may incorporate wire coils 488. The second fore turbine blades 472*fx* may incorporate magnets 489. Oncoming wind flow (W) may rotate the blades of first fore turbine 472*fw* (powering the shaft 475*h*) clockwise; then flows to rotate the blades of second fore turbine blades 472*fx* (free-spinning) anti-clockwise. Such that when the twin turbines in close proximity counter rotates against each other the embedded elements 488 and 489 in the moving turbine rotor blades may generate electricity. The same configuration applies to the first aft turbine 472*ay* and second aft turbine 472*az*. Oncoming wind exiting fore turbines 472*fw* and 472*fx* flows over to rotate the first aft turbine 472*ay* (free-spinning) clockwise; then flows over to rotate the second aft turbine 472*az* (powering the yoke 484) anti-clockwise. Two generation sources comprises: (a) twin rotors of wire coil ring 474*h* and magnet ring 476*h*; (b) embedded wire coils 488 and magnets 489 present in the turbine blades 472*fw*; 472*fx*; 472*ay*; 472*az*.

Likewise FIG. 4H illustrates twin turbine rotors 472*f* (fore) and 472*a* (aft) mounted on fixed pillar 469 and adjustable pillar 469*m*; which counter rotates against each other to produce power by means of embedded wire coils 488 and magnets 489. A swivel joint 468 may be incorporated into the top of fixed pillar 469 near generator module 473; while movable pillar 469*m* may be shifted by means of a motor in a semi-circular arc shaped base 459*c* configured into concrete pedestal 459. This enables shifting of the turbines to face the wind. Two generation sources comprises: (a) conventional stator 474 and rotor 476 assembly of generators 473; (b) wire coils 488 and twin magnets 489 embedded into the turbine blades 472*f* and 472*a*.

FIG. 4I illustrates the sectional front view of a variant version of vertical axis turbine 477*v* wherein, a plurality of counter-rotating sections of said turbine may be configured to operate as a single unit 477*v* for producing electricity by means of twin rotors powered generators 474*r*; 476*r*; and disc generators 486*r*; 487*r* mechanisms; using both vertical axis generating elements comprising: rotor wire coils 474*r*; rotor magnets 476*r*; and flat discs of rotor wire coils 486*r*; and rotor magnets 487*s*. The entire apparatus 477*v* may be

set up on fixed pillars/or, it may be lifted into high altitude by means of tether 50*at* affixed to HAV-400 wind crane. Section A and C may be configured to revolve clockwise; while section B and D may be configured to rotate in an anti-clockwise direction. The vertically aligned rotor shaft 475*v* ran from the topmost vertical axis generating elements 486*r*; 487*s* (above section Ag) to the bottom most generating elements 486*r*; 487*s* (below section Dg). Shaft 475*v* bore the entire weight of apparatus 477*v*. An orifice 459 may be configured into the magnet discs 487*s* and 487*r* to enable passage of vertical shaft 475*v*. Electricity generated may be routed via tether-cable 478.

The vertical axis generating elements may comprise of: rotor shaft 475*v* affixed with wire coils 474*r*; and rotor casings 477*c* affixed with magnets 476*r*. In section A and C; rotor shaft 475*v* driven by the turbine blades may be configured to turn in a clockwise direction. In section B and D; shaft 475*v* may be integrated with a layer (ring) of wire coil 474*r*; surrounded by a layer (ring) of magnet 476*r* integrated into rotor casings 477*c* of turbine blades 477. Casing 477*c* is equivalent to yoke 484 of FIG. 4C and FIG. 4D. The turbine blades 477 may be configured to turn casings 477*c* and layer (ring) of magnet 476*r* in an anti-clockwise direction. This counter revolving movement provided by the (a) rotating shaft 475*v* to the rotor wire coils 474*r* (clockwise); and the (b) rotating turbine casing 477*c* to the rotor magnet rings 476*r* (anti-clockwise) may be used by the vertical axis generators 477*v* to produce electricity.

The horizontally aligned disc generating elements AB; BC; CD; configured in between sections A; B; C; D; may also be used to produce electricity; from the counter rotational movement of the rotor wire coiled discs 486*r* and the rotor magnet discs 487*r*. Vertical axis disc generator AB uses the clockwise movement of section A turbine to drive the wire coil disc 486*r*; and the anti-clockwise movement of section B turbine to drive the magnet disc 487*r*. The topmost and bottom most discs generators Ag and Dg may comprise of: rotor wire coil discs 486*r* and stator magnet discs 487*s*. Two generation sources comprises: (1) wire coils 474*r*; magnets 476*r*; (2) rotor wire discs 486*r*; rotor magnet discs 487*r*; and conventional stator-rotor setup 486*r*; 487*s*.

An airborne ecosystem 500 for extraction of high altitude wind energies for generation of renewable energies; comprising the integration of: (1) an aerial system of heavy lifting drones HAV-400; with (2) heavy lifted loads. Wherein said heavy lifting apparatus comprises HAV-400 wind cranes. Said heavy lifted loads comprises: (a) wind turbines: 471; 477*v*; 490*h*; 490*d*; 490*q*; 500*b*; 500*c*; 500*d*; multi-staged counter-rotating wind turbines 500*a*; (b) a high altitude wind energy harvesting system 510*a* comprising airborne Station X, Station Y; (c) and an improved system 76*aa* with a multitude of flying windbags 30*ap* spearheaded by a drone HAV-400; a drone HAV-100*aa*. This ecosystem 500 may be illustrated by FIG. 5A to FIG. 5M; in combination with FIG. 4A to FIG. 4G; FIG. 4I; FIG. 6A to FIG. 6N; FIG. 6P to FIG. 6Q; and FIG. 8B.

FIG. 5A to FIG. 5M illustrates a variant system 500*a* to 500*d* of Airborne-wind-Turbine-Generators-500*a* herein designated as AWTG-500*a* to 500*d*; lofted into high altitude by means of HAV-400 wind-cranes to harness and to harvest high altitude wind energy. The Airborne-wind-Turbine-Generators AWTG-500*a* being lifted may be configured to be vertically disposed; or inclined at an angle relative to the wind direction (refer FIG. 5C; FIG. 5D; FIG. 5J; FIG. 5M). This systemic variability may be required to adjust to changes in wind speed/energy; turbulence; loading; for operational purposes and practicability of application. At a

certain angle of incline, wind-lift caused by the upward thrust of the wind current on the AWTG-500a may reduce its weight; or load on the HAV-400; thus partially balancing out the weight of AWTG-500a.

FIG. 5A to FIG. 5D illustrates a system comprising of a multi-staged counter-rotating airborne wind turbine generator AWTG-500a mounted on a single plane; with multiple rings of generating mechanisms 491 comprising: concentrically arranged rings of turbine blades 492; rotor wire coils 493; rotor magnet coils 494. One rotating circular ring 491 mounted inside/or outside of another rotating circular ring 491. FIG. 5A illustrates the front view of a vertically lifted wind turbine 500a; FIG. 5B illustrates the cross-sectional plan view of FIG. 5A. FIG. 5C illustrates a side view of FIG. 5A; while FIG. 5D illustrates a side view with the turbine lifted at an inclined position.

The structural configuration of conventional wind turbines comprises stators and rotors. Wherein the configuration of present invention comprises: dual rotors; no stators. Dual rings of rotor coils and rotor magnets; turning the generating mechanisms in two opposing directions of rotation. To this end wind energy harnessed by means of such dual rotors may be used to produce counter-rotational movements in both rings of the rotor coils. With reference to FIG. 5A to FIG. 5B viewed from the center hub 496 moving towards the periphery, the outermost edge 501; the configuration of AWTG-500a may be described as follow: (a) Stage 1 turbine-generator ring 491a comprising: a circular ring of turbine blades 492a; configured with a ring of rotor wire coil 493a at the outer edge; and a ring of rotor magnet 494a surrounding a stator wire coil 495s at the hub 496. (b) Stage 2 turbine-generator ring 491b comprising: a circular ring of turbine blades 492b affixed to a ring of wire coil 493b at the outer edge; and a ring of magnet 494b at the inner edge. (c) Stage 3 turbine-generator ring 491c comprising: a circular ring of turbine blades 492c bearing a ring of wire coil 493c at the outer edge; and a ring of magnet 494c at the inner edge. Central hub housing 496 may be configured with conventional rotor magnet 494a and stator wire coil 495 assembly to produce electricity. While the generation mechanism at the circumference of apparatus 500a may comprise of a ring of rotor wire coil 493c and stator magnet ring 497s. Rotor wire rings 493 and rotor magnet rings 494 rotates and moves in extended guide sleeves 498 of framework girders 499; keeping them in position. Roller bearings and ball bearings may be used where applicable.

The whole wind-turbine-generator apparatus 500a may be slotted into and securely mounted in a circular body clamp 501; supported by a framework comprising girders 499; struts 502; etc. Any number of girders 499 and struts 502 may be used to support the apparatus as desired. Circular body framework 501 may be configured as a clamp mechanism gripping tightly onto apparatus 500a. Hub 496 and body clamp 501 may be configured with provisions for line (21aa to 21ad) attachments such as lifting rings 501c for use with lifting clamps and hooks; winches 59aa (for line adjustment); rudders 69, rudder-fins 84aa; fins 85aa and winglets 85aa; for computerized 503 directional control and orientation. Electricity may be generated when one power generating ring 491 comprising: a ring of turbine blades 492 mounted with a ring of rotor wire coil 493 and a ring of rotor magnet 494 at each end; rotates against the counter rotating components of another ring(s) 491 mounted adjacent to it in close proximity. Or, rotates against fixed stator components such as the stator wire coil 495 located at the central hub 496; and the outermost stator magnet ring 497 located at the edge of apparatus 500a. Optionally, stage 3 turbine blades

492c may be configured with rings of magnets 494c at both the inner and outer edges; surrounded by a stator wire ring 497 at the outermost edge of AWTG-500a. Such flexibility of configuration may be used to optimize design and efficiency.

The stage 1 turbine-generator ring 491a; and stage 3 turbine-generator ring 491c may be configured to rotate in the same direction, with stage 2 turbine-generator ring 491b (located in between stage 1 and 3) configured to rotate in the opposite direction. For example: if stage 1 and stage 3 are configured to rotate clockwise; stage 2 shall be configured to rotate anti-clockwise. Or conversely configured. Such a counter-rotational structural configuration enables doubling of the relative speed of rotation between the stage 2 turbine-generator 491b (anti-clockwise); and that of stage 1 turbine-generator 491a (clockwise); and stage 3 turbine-generator 491c (clockwise). And vice-versa. Thus rotational movement and relative speed between the stage 2 turbine-generator 491b (rotating anti-clockwise); and that of stage 1 and stage 3 turbine-generators 491a; 491c (rotating clockwise) may be doubled. This may increase the efficiency and productivity (e.g. doubled power generating capacity) of the Airborne-wind-Turbine-Generator-500a in producing renewable electricity. Multiple stages of counter-rotating AWTG-500a in excess of three stages (as illustrated); for example: five stages; ten stages; etc. may also be configured for use.

FIG. 5C illustrates the side view of an AWTG-500a lifted in a vertical position; while FIG. 5D illustrates the side view of an AWTG-500a lifted in an inclined position by means of HAV-400 wind crane. Tether line 50aa and a plurality of bridle lines 21aa may be used to enable lifting of the units into a suitable height for harnessing high altitude wind energy. FIG. 5E to FIG. 5G illustrates the front view of variant Airborne-wind-Turbine-Generator 500b; 500c; 500d. FIG. 5H illustrates the cross-sectional side view 5H-5H; while FIG. 5I illustrates the cross-sectional side view 5I-5I. FIG. 5H and FIG. 5I illustrates two possible arrangements in which the apparatus as shown in FIG. 5E to FIG. 5G may be configured. Wherein AWTG-500b; 500c; 500d; may be configured as illustrated in FIG. 5H (single plane), FIG. 5C and FIG. 5K. Or arranged side-by-side in a port and starboard configuration as illustrated in FIG. 5I; FIG. 5J (dual plane); and/or in an over-under configuration (inclined lift); if FIG. 5J is lifted in an inclined position as illustrated in FIG. 5D and FIG. 5M.

The apparatus may be configured to generate electricity by means of a centrally located hub 496 in the middle; and at the periphery 497e; 497f; 497g. Hub 496 may comprise of rotor magnet ring 494e; 494f; 494g; and stator wire coil 495e; 494f; 494g/or standard stator 474 and rotor 476 coils (refer FIG. 4A). The generation mechanism at the circumference of the turbine may comprise of a ring of rotor wire 493e; 493f; 493g and a ring of stator magnet 497e; 497f; 497g. The inner ring of rotor wire 493e; 493f; 493g mounted at the tip of the turbine rotors 492e; 492f; 492g revolves around an outer coiled ring of magnet 497e; 497f; 497g; mounted in a ring at the outermost edge 473e; 473f; 473g. Optionally in a vice versa arrangement; the configuration or location of generating mechanism comprising: stator wire ring 495 and rotor magnet ring 494 may be swapped.

FIG. 5E, FIG. 5F and FIG. 5I illustrates a system wherein generating mechanisms comprising rings of rotor wire 493f; 493g and rings of coiled stator magnet 497f; 497g; may be integrated into a single unit protected by generator housing 473f; 473g. FIG. 5A illustrates a configuration comprising exposed individual rings of rotor magnet 494; and coiled

stator wire **493** components. FIG. **5H** illustrates the side view of a standard single turbine-generator **500b**; **500c**; **500d**; configured with rotor **494e** and stator **495e** assembly in the central hub **496e**. The ring of rotor blades **492e** may be affixed with a ring of rotor wire **493e** at the edge; surrounded by an external ring of stator magnet **497e**.

FIG. **5I** illustrates a variant configuration of FIG. **5H** wherein dual units of turbine-generators **500b**; **500c**; **500d**; may be configured side-by-side, vertically oriented and aligned in a fore and aft position (refer FIG. **5J**) or in a port-starboard configuration and in close proximity to each other, facing the wind. The blades of twin turbines **492f** (fore); **492g** (aft) may be configured to counter-rotate against one another. The counter-revolving turbine blades **492f**; **492g** may incorporate/or be embedded with power generating elements comprising: rotor wire coil **488** and rotor magnets **489**. For example: if the fore turbine blades **492f** embedded with wire coils **488** rotates clockwise; the aft turbine blades **492g** embedded with magnets **489** shall rotate in an anti-clockwise direction. These embedded rotor wire coils **488** and rotor magnets **489** present in counter-revolving turbine blades **492f** and **492g** may also be used to produce electricity. Just like the standard rotor **494f**; **494g**; and stator **495f**; **495g** assembly in the central hub **496f**; **496g**.

In this configuration, electricity may be produced from three generation mechanisms comprising: (a) standard rotor magnet ring **494f** (and **494g**) and stator wire coil **495f** (and **495g**) in the hub **496f** (and **496g**); (b) rotor wire coil ring **493f** (and **493g**); and stator magnet ring **497f** (and **497g**) at the circumference; and (c) counter-rotational movement of wire coils **488** and magnets **489** embedded into turbine blades **492f** and **492g**. Electricity **456** produced from all of the three above points of generation may be collected and channeled into tether-cables **478** to a mooring buoy **508** for conveyance to processing plants on floating platforms.

FIG. **5J** illustrates a variant version of FIG. **5I** wherein twin units of ATG-**500a** (mounted on dual planes) may be combined together in a side-by-side/or, in an over-under configuration to function operably as a single unit. Incorporation of embedded rotor wire coils **488** and rotor magnets **489** into turbine blades **492** as illustrated by FIG. **5I** may enable improved productivity and efficiency. The apparatus may be lifted into high altitude in a vertical/or inclined position by means of HAV-**400** wind crane using a plurality of bridle lines **21aa** and tether line **50aa**. FIG. **5K** illustrates system **500**; showing the front view of a wind-crane HAV-**400** lofting a plurality of vertically disposed turbine generators **471**; AWTG-**500a**; **500b**; by means of tether **50aa** facing the oncoming wind. FIG. **5L** illustrates a customized storage rack-container **504** with partitioned slots **505** for keeping the ATGs-**500**. Demobilized units may be lowered and slotted back into rack **504**.

FIG. **5M** illustrates system **500**; wherein, an inclined AWTG-**500b** may be lifted into high altitude by means of a HAV-**400** wind-crane. The tether **50aa** may be linked to bridle lines **21aa**; **21ab**; **21ac**; **21ad**; at common joint **506**; with camera **507** attached. Lines **21aa** to **21ad** may be attached to the external framework **501** of turbine-generator **500b** by means of lifting lugs and rings **501c** and their lengths adjusted by means of winches **59aa**. Electrical power generated may be routed by means of cable-tether **478** to reel system **52aa** mounted on a seaborne mooring buoy **508**; which may in turn be routed by means of submarine cables **457u** to floating electrolyzer plants **509s** abroad FPSO vessel **511** for producing hydrogen gas. Cable **457u** may also route the electricity to a land based hydrogen gas generation plant **509t**. Specially configured Floating

Production Storage Offloading (FPSO) vessels **511**; sited proximate to buoy **508** provides a floating platform for producing hydrogen gas/or for other means of energy conversions; storage; transfer of products to seaborne carriers; etc. The renewable electricity generated may also be channeled by means of submarine cables **457u** to land based transformer stations, overhead cables **457** and towers **458** for transmission to consumers;/or to land based electrolyzer plants **509t** for conversion, storage, transfer, etc. Such electrolyzer plants **509s** may also be sited on fixed leg platforms **290aa**/or borne by mobile floating production rigs and flatbed vessels comprising: semi-submersible platforms **292aa**; flatbed platforms **293aa**; inflatable floating bodies **294aa**; anchored to the seabed piles **545** by means of subsea cables **295aa**; supported by mother ships **289aa**; factory ships **296faa**; tankers **296taa**; etc. Such mobile floating platforms/or bodies may also be moored by means of lines **512** to floating buoys **508**; which may in turn be secured by means of subsea cables **295aa** to undersea pillars **545**; piles **562**; beams **563**; plugs **564**; etc. (Refer: System **300** of FIG. **13I**; FIG. **13D** of U.S. Pat. No. 8,963,362). The external frame of the AWTG-**500b** may be equipped with computerized **503** directional control surfaces comprising: rudder-fins **84aa**; fins and winglets **85aa**; which may be manipulated to orientate the module into a desirable; optimal position relative to the wind direction and altitude.

Computerized system **503** abroad may be configured for total operational control of AWTG-**500b** comprising: self-alteration, self-alignment and automated adjustment of system **500b**'s orientation and position relative to the wind direction; wind speed; optimized energy production; used to monitor AWTG-**500b**'s system performance; faults and deficiencies with the help of cameras **507**. And for liaison and feedback with surface based/or ground based computerized smart control systems such as the DCS; integrated with Artificial Intelligence (AI).

FIG. **6A** to FIG. **6N** illustrates an airborne high altitude wind-energy extraction system **510a** for deploying a plurality of windbags **30aa**. FIG. **6O** illustrates a deep-sea-diving ocean-energy extraction system **510u** for deploying a plurality of water-bags **40aa**. Systems **510a** and **510u** may be deployed together in the combined wind and water energies extraction plant **300** (previously disclosed in FIG. **13I** of U.S. Pat. No. 8,963,362)—a marine eco-system specially configured for the production of renewable energies. FIG. **6A** to FIG. **6N** illustrates an airborne system **510a**; while FIG. **6O** illustrates a seaborne system **510u**; wherein said disclosure may comprise parallel systems to the riverine hydro-energy extraction plant **310** (previously disclosed in FIG. **14A** to **14G** of U.S. Pat. No. 8,963,362).

However, compared to riverine system **310** executed on land; airborne system **510a** and deep-sea diving system **510u** are much more complex and difficult; and operates in an occupational environment more hazardous than run of the river systems. Requiring the use of apparatus, equipment, systems, methods and techniques as disclosed in FIG. **6A** to FIG. **6N**. The airborne system **510a** requires much more complex light weight components, HAV-**400**; air-bridges **429p**; **429r**; radio-frequency activated sub-systems. While the seaborne system **510u** requires semi-submersible platforms comprising: upstream surface Station U; downstream bottom Station V; supporting surface Station W; secured by cables **295aa** to pillars **545** piled into the seabed **537**; or, to suction cups **550** affixed to the sea-floor **537**; submarine boats **220aa**; personal submersible vehicles **220aa**. The combined airborne system **510a** and seaborne system **510u** may also be integrated with other components of the marine

ecosystem **300** comprising: fixed leg platforms **290aa**; mobile floating production rigs and flatbed vessels; semi-submersible platforms **292aa**; floating flatbed platforms **293aa**; inflatable floating bodies **294aa**; mooring buoys **508**; electrolyzer plants **509** aboard FPSO **511**; anchored by means of undersea cables **295aa** to pillars **545**; piles **562**; beams **563**; plugs **564**; etc. in the seabed **537** and seamounts **555**; supported by mother ships **289aa**; factory ships **296faa**; tankers **296taa**; etc. deep-sea diving and operation components; sonar activated sub-systems; etc. including other hi-tech equipment such as advanced Artificial Intelligence computers; specialized equipment and much more complex sub-systems than the riverine extraction plant **310**. Actionable solutions much more difficult to execute than the prior art disclosure. Relevant components disclosed herein may be adapted for use with system **310**.

FIG. 6A illustrates an overall view of the airborne high altitude wind energy extraction cum power generation system **510**; whereas, FIG. 6B and FIG. 6C illustrates more detailed arrangements of Station X, **429p** (Start-of-Run) SOR point **16aa**; and Station Y, **429r** (End-of-Run) EOR point **288aa**. For ease of description these two points may be referred to as Station X and Station Y. Wherein, both Stations X and Y may be lofted; carried up into high altitude by means of a plurality of HAV-**400** wind-cranes. Optionally, tethered **46aa** HAVs-**45aa**; balloons; airships-**45aa**; aerostats-**45aa** and blimps **45aa** may also be used. Station X may be located upwind of Station Y. Station Y may be located at the same altitude as Station X; or Station Y may be located at a higher altitude than Station X; enabling windbags **30aa** to engage wind of much higher speed and energy as they ran from Station X (SOR) to Station Y (EOR). One pair of guide lines (**304ap'**; **304ap''**) forms a complete loop from Station X to Station Y for power run of windbags **30ap**; and from Station Y back to Station X (**304ar'**; **304ar''**) for retraction, return, retrieval of windbags **30ar**. A multitude of such pairs of guide-lines (forming lane A, lane B, lane C, etc.) may be configured running to and from Station X and Station Y. With the windbags **30aa** used and reused repeatedly within the loop of running lanes (A; B; C). Generating renewable energies from High Altitude Wind Power.

Windbags **30ap** may be flexibly connected to a pair of guide lines marked **304ap'** and **304ap''** (which forms aerial runway Lane A) by means of a pair of swivel holding rings **308ap'** and **308ap''**. At the air-bridge **429p** of Station X (a more advanced form of work platform **47aa**) windbags **30ap** with inflated ring **22ap** and air-ribs **277ap** may be released through the SOR gates **520p'**; **520p''**; running from Station X to Station Y along Lane A formed by guide lines **304ap'** and **304ap''**; pulling tether **50aa**; powering generator **55ag**. At the End-of-Run phase near Station Y, air may be released from the exhaust port **532** of pressure control sub-system **530**; deflating ring **22ap** and air-ribs **277ap**. Sub-system **530** may be activated by means of (RF) radio frequency transmission from a proximity transmitter **299raa** located on work bridge **429r** to receiver antenna **534** (refer FIG. 6K; FIG. 6L). The collapsed, depowered windbag **30ar** may be released through the EOR gates **520r'**; **520r''**; of air-bridge **429r** Station Y. The returning windbag **30ar** may be retrieved by means of tether **50ar** wound in by line reel **52aa** and retract motor **49aa**; via retraction guide lines **304ar'** and **304ar''**; moving from Station Y to Station X.

FIG. 6D illustrates a much more detailed arrangement of Station X, than FIG. 6B for launching windbags **30ap** at air-bridge **429p**. While FIG. 6E illustrates a much more detailed arrangement of Station Y, than FIG. 6C for depow-

ering windbags **30ar**; and for their return to Station X. FIG. 6D and FIG. 6E also illustrates details of the gated sub-system **520p** and **520r** (refer FIG. 6H to FIG. 6J) at the SOR and EOR phases for passage of windbags through these anchoring points. Wherein said plurality of windbags **30aa** are used for generation of power; returned to the starting point; reused and recycled repeatedly in a closed loop.

FIG. 6D illustrates the detailed layout of the air-bridge **429p** of Station X for launching windbags **30ap**. This is the Start of Run (SOR) point **16aa** where incoming windbags **30ap** are prepared; readied for deployment; and launched for a power generating run from Station X to Station Y. Collapsed incoming windbags **30ar** returning from Station Y arrives by means of dual returning guide lines **304ar'** and **304ar''**; with the port and starboard holding rings **308ar'** and **308ar''** in close proximity to each other due to the collapsed state of windbag **30ar**. At Station X the pair of guide lines **304ar'** and **304ar''** may be enjoined to a pair of "Y"-shaped solid state frames **515p'**; **515p''** at joints **514r'**; **514r''**. Said port and starboard guide lines **304ar'** and **304ar''** may be unwrapped/or embedded inside of a thick solid state frame **515p'** between the points **514r'** to **514p'**"; and frame **515p''** between the points **514r''** to **514p''**". The "Y"-shaped frames **515p'**; **515p''** may be held in position by the dual banks of the gated sub-system **520p'**; **520p''**. Components **521** and **522** of sub-system **520p** may be configured along the windbags **30ap** run-way (Lane A) formed by port and starboard guide lines **304ap'** and **304ap''** embedded in frames **515p'** and **515p''**. Dual guide lines **304ap'**; **304ap''** in turn forms an airborne run-way for the guided flights of windbags **30ap**; which for reference purposes may be designated as: "Lane A"; "Lane B"; "Lane C"; etc. Said "Y" shaped frames **515p'**; **515p''** may be spread out reflecting the actual diameter (e.g. 2 m) of the inlet port ring **22ap** of the inflated windbag **30ap** as configured.

Solid frame **515p** comprises a component of the guide lines **304ap** system. It does not form part of the structure of Station X or Y. Guide lines **304ap** running from Station X to Station Y provides a guided aerial running pathway for windbags **30ap**; pulling tether **50ap** to generate power by means of generation system **55ag**. Returning guide lines **304ar** running from Station Y to Station X provides a means for retrieving depowered windbags **30ar**. Retracted by means of tether **50ar** wound back by spool **52ar** and motor **49ar**. Said guide-lines **304aa** system forms a round loop from Station X to Station Y; then back again from Station Y to Station X. In this loop windbags **30aa** rotates; going from one phase to another; from one cycle to another repetitive cycle.

Though solid frames **515p** and **515r** does not comprise part of the structure of Station X; Y; it may be flexibly and securely connected to said structures by means of gated sub-system **520** and affixed holder-stands **525**. At station X, as the windbag **30ar** moves past point **514r'**; **514r''**; frame **515p'**; **515p''** spreads out and widens the "Y" shaped gap in between the two incoming guide lines **304ar'**; **304ar''**. Cover **536** may be removed from the external of windbag **30ar** and/or retract line **33ar** disengaged from clip **533** at point **31aa** by means of robotic appendages **522** comprising arms **526**; hands **527**; fingers **528**; and thumbs **529**. Depowered windbag **30ar** is freed and opens up. Pressurized air may be injected into inlet port **531** of controller **530** by means of hand held (robotic limbs **522**) compressed air nozzle **535**; inflating inlet port ring **22ap** and air-ribs **277ap**. Windbag **30ap** passes through the electronic gated sub-system **520p** before being released to fly to Station Y. Sub-system **520p** and **520r** provides the two main contacts and only anchoring

points securing guide lines **304aa** in between Station X and Station Y. Sub-system **520p** allows safe and secure passages of windbags **30ap** through the anchored guide-lines **304ap'**; **304ap''** at the SOR point **16aa**. Sub-system **520r** allows safe and secure passages of windbags **30ar** through the anchored guide-lines **304ar'**; **304ar''** at the EOR point **288aa**. Ensuring positive physical contact between the guide lines (**304ap** and **304ar**) and the air-bridges (**429p** and **429r**).

FIG. 6E illustrates a more detailed layout of the air-bridge **429r** of Station Y for depowering windbags **30ap**. This is the End of Run (EOR) point **288aa** where incoming windbags **30ap** are depowered and processed for return to Station X (SOR). The port and starboard guide lines **304ap'** and **304ap''** joined the solid frames **515r'** port side and **515r''** starboard side at points **514p'** and **514p''**; thereafter the twin pieces of solid frame **515** port and **515** starboard may be curved to converge together in proximity to each other. Securely held in position by locked gate sub-system **520r** affixed to holder-stands **525** which forms part of air-bridge structure **429r**. After the gated sub-system **520**; solid frames **515** may be curved to bend downwards; joining port guideline **304ar'** at point **514r'** and starboard guide-line **304ar''** at point **514r''**. Guide-lines **304ar'** running from Station Y may be connected to the port solid frame **515r'** of Station X air-bridge **429p** at point **514r'**; and **304ar''** connected to the starboard solid frame **515r''** at point **514r''**.

In proximity to EOR Station Y air-bridge **429r**, incoming windbag **30ap** may be depowered by means of apparatus **530**; activated by RF signals from apparatus **299raa**. Inlet port ring **22ap** and air-ribs **277ap** collapsed. Gear box **53ag** of generator **55ag** may be freed. The collapsed windbag **30aa** may be routed to apparatus **520ar** where it passes through the plurality of gates **521**; **522** one at a time till it reaches the downward bending portion of frame **515r'**; **515r''**. The returning windbag **30ar** is reeled in by means of tether **50ar** and retract motor **49ag**; from Station Y to Station X.

Optionally, after exiting gated sub-system **520r**, holding ring **308ap'** may be shifted from port guideline **304ap'** to starboard guideline **304ar''** by means of robotic limbs **522**; prior to the return journey from Station Y to Station X. Upon arrival at Station X, this maneuver may be reversed. The holding rings **308ar'** may be shifted from the port frame **515p'** holding guideline **304ar''** back to starboard frame **515p'** holding line **304ap'**; prior to entering gated sub-system **520p**. Such a maneuver avoids interference of lines **50ap** and **50ar** between a multitude of running and returning windbags **30aa**.

FIG. 6F illustrates an optional configuration wherein twin retract lines **304ar'** and **304ar''** may be combined together and merged into a single line **304ar** for returning depowered windbags **30ar** from Station Y to Station X. Such a structural configuration eliminates problems of line interference; entanglements; knots formation; etc. between lines **50ap** in power run and line **50ar** in retraction phase. Because multiple windbags and tether lines **50ap**; **50ar** may be moving to and fro between Station X and Y along a single lane A at any one point in time. And along any of the other lanes B; C; D; etc. To this end the dual pieces of "Y" shaped solid frame **515r'**; **515r''** may be merged into one piece **515r** at the confluence of the two split forks **515r'** and **515r''** at Station Y. Apparatus **515p'**; **515p''** may be similarly modified at Station X. At Station Y, upon outgoing windbags **30ap** having cleared the gates **520**; robotic limbs **522** may be used to effect the switching of the swivel rings **308ap'** and **308ap''**. From the forked frame **515'** and **515''** holding guide lines **304ap'** and **304ap''**; over to the merged frame **515r**

holding a single combined guide line **304ar**. This process may be reversed at Station X wherein, depowered incoming windbags **30ar** may be transferred from merged portion of frame **515r** holding line **304ar**; to the forked portion of frame **515'** and **515''** holding lines **304ap'** and **304ap''** by means of robotic limbs **522**. Readied and prepared for the power up phase; passed through the gated sub-system **520**; and put on hot standby.

FIG. 6G illustrates use of a tall relief feature/or topographically advantageous geological features like for example: a high mountain top **516** adapted as a high altitude ground Station G. The relief **516** may be suitably modified, converted and configured with structural features **516m**; for use as a platform (Station G) for launching windbags **30ap** to an airborne air-bridge **429r** (Station Y) supported by a plurality of HAV-400 wind-cranes. Ground Station G may replicate Station X of FIG. 6A to 6D; except that it may be sited on solid ground at a high altitude (e.g. 2 km). It may also comprise of a fixed platform **517** configured with flexibly adjustable side extensions **517x** which may be moved around whenever needed to face the wind direction for optimized wind energy capture; extraction and renewable energy production. Motorized mobile side extensions **517x** supported by beams **518** may provide extended length; increasing the useful work area. Likewise, an air-bridge station suspended in between a plurality of mountain peaks may also be used together with an airborne air-bridge (Station Y).

FIG. 6H to FIG. 6J illustrates components of sub-system **520** comprising mechanical clamps **521** and robotic limbs **522** for working in an environment fraught with extremities—high altitude and deep-sea work stations. FIG. 6H illustrates a mechanized hydraulic clamp cum robotic holder **521** for securing a guide-line **304aa** embedded inside a solid state frame **515**. The two piece clamp **519a** and **519b** may be activated by means of mechanized push rods **523** using hydraulic or pneumatic pressure from a pump **524a** and reservoir **524**. Clamps **519a** and **519b** may include magnetized locks to maximize locking hold. Apparatus **521** may be securely affixed to holder-stand **525** which forms part of the air-bridge structure **429p**; **429r** of Station X and Station Y.

FIG. 6I illustrates a side view; while FIG. 6J illustrates a front view of a variant apparatus **522** of sub-system **520**. Mechanical limbs/or appendages **522** may consist of touch sensitive activated mechanisms integrated with computerized-mechanized robotic limbs/or appendages **522** comprising: robotic arms **526** (lower arm **526'**; upper arm **526''**); hands **527**; fingers **528**; and thumbs **529**; integrated with electronic eyes (cameras **509**) and artificial intelligence (AI). The figures illustrates robotic limbs **522** which may be configured with 4 fingers **528** and two thumbs **529**; the robotic limb **522** securely holding a thick solid state frame **515** with a guide-line **304aa** embedded inside. Two thumbs pressing on the four fingers provides superior grip and better hold than a single thumb; with the thick solid frame **515** providing a larger area and much better holding grip than a single strand of line **304aa**. Frame **515** may comprise of: glass; fiber-glass; plastics; carbon-fibers; metal; etc. Similar robotic limbs **522** different in arrangement and form may also be configured to do useful work. Such artificial robotic limbs mimicking the extreme dexterity of the human limbs integrated with cameras and computerized Artificial Intelligence provides the best equipment and tools required to perform repetitive menial tasks in dangerous workplaces. Such as high altitude flight and deep sea diving, working in an environment fraught with extreme difference in pressure, temperature and oxygen deficiency. Where prolonged expo-

sure may not be tolerated by human bodies. Apart from sub-system 520, the computerized-mechanical robotic limbs 522 comprising: robotic arms 526; hands 527; fingers 528; thumbs 529; may also be used for performing other delicate tasks on the air-bridge 429p and 429r; Station X and Station Y; used in support of other components of present invention and parent U.S. Pat. No. 8,963,362.

Gated sub-system 520 may comprise 3 individual pairs of gate apparatus 521 and/or 522 configured directly opposite each other along Lane A. One apparatus mounted on each side of the solid state frame 515'; 515" embedded with guide lines 304aa'; 304aa"; each pair of apparatus arranged one facing the other; aligned along the port side 515' and the starboard side 515" of said gate 520. Spaced out at an optimum distance; a multitude of such pairs of apparatus 521 and/or 522 greater than 3 in number (maybe up to 10) may be configured; in order for the sub-system 520 to work efficiently. A synchronized sequence of opening and closing said electronic gates 520 enables phased passage of the swivel holding rings 308aa (affixed to windbags 30aa) through the individual apparatus 521 or 522 of gates 520p; 520r. One gate at a time. The first gate to open being gate 1; with gate 2 and 3 closed. Then with gate 1 and 3 closed; gate 2 opens. Then with gate 1 and 2 closed; the last gate, gate 3 opens. Then with all the gates closed, the sequence started over again for a refreshed "new" incoming windbag 30aa.

FIG. 6K illustrates a puffed up windbag 30aa with inflated inlet port ring 22ap and air-ribs 277ap; outfitted with apparatus 530; a pair of swivel holding rings 308ap'; 308ap" at the sides; and bag cover 536 with retract line 33ar at the rear. FIG. 6L illustrates a computerized electronic air pressure control sub-system 530 for controlling the inflation and automated deflation of ring 22ap and air-ribs 277ap. Air may be pumped into the inlet port 531 by means of a hand held (robotic limb 522) air nozzle 535 to inflate windbags 30ap prior to being deployed. Equipped with radio frequency (RF) activated depressurizing system, controller 530 may be activated by means of RF transmitter 299raa and receiver antenna 534 to deflate windbags 30ap via exhaust port 532 as it approaches in proximity to gated sub-system 520r of Station Y. Flexible antenna 534 may be integrated into ring 22ap; or windbag 30ap. Transmitter 299raa may be mounted on air-bridge 429r. Apparatus 530 may also be used for RF activated depowering (299raa; 534) of the overall airborne wind power generation system 510 in time of emergency: e.g. approaching storms; faulty equipment; emergency shut down and demobilization of the whole plant, etc.

FIG. 6M illustrates a collapsible-extendable light weight cover 536 for keeping the depowered windbags 30ar in a collapsed form for passage from Station Y back to Station X. The cover 536 may be extended over windbags 30ar by means of robotic limbs 522 comprising robotic arms 526; hands 527; fingers 528; and thumbs 529; as the windbags 30ar passes through the gates 520r of Station Y. At Station X, as windbag 30ap approaches gate 520p; cover 536 may be collapsed and air injected into port 531 by means of hand-held (robotic limbs 522) air nozzle 535; inflating the ring 22ap, air-ribs 277ap. Windbag 30ap passes through gate 520p and is ready for the power run from Station X to Station Y. Optionally, at Station Y, a short retract line 33ar (aft) affixed to the apex 32aa of windbag 30aa may be pulled by robotic limbs 522 and secured to joint 31aa (fore) by means of a spring-loaded clip 533; keeping bag 30aa in a depowered state. Joint 31aa being the attachment point between tether 50aa and bridle lines 21aa. A piece of string

33ar affixed to point 32aa on the external of windbag 30aa; or the rear of cover 536; pulled and secured to clip 533 by robotic limbs 522 may serve the same purpose.

FIG. 6N illustrates sub-system 540; for coordinating the running sequence of the multitude of windbags 30aa. When a windbag 30aa starts its power run from Station X to Station Y; the driven unit 55ap may be moved from point marked X (514p'; 514p") to Y (514r'; 514r") on the ground. During the windbag retraction phase from Station Y to back to Station X; the driven unit 55ar may be moved from point Y (514p'; 514p") to point X (514r'; 514r"); the driven unit 55ar then waited for its turn before moving to point X (514p'; 514p") to start its next power run again.

For ease of identification in FIG. 6A to 6N, apparatus related to power generating phase from Station X to Y had been assigned a letter "p"; while apparatus related to the return; retrieval; or retraction phase from Station Y to X had been assigned a letter "r". For example: letter "p" in windbag 30ap denotes a bag in "power run" phase. Letter "r" in windbag 30ar denotes a bag in "retraction" phase. Windbag 30aa denotes reuse of a previously used number from the parent U.S. Pat. No. 8,963,362.

Windbags 30aa attached to guide-cables, wire-lines or guide-lines 304aa may be used for harnessing and extracting high altitude wind energy; said windbags running from one airborne workstation/or air-bridge to another: e.g. Station X to Station Y. Work stations X and Y may be airlifted by means of a plurality of HAV-400 wind-cranes; and kept in a relatively stable location and position. Station X and Station Y may be located at the same altitude. Or, Station X may be located at a height of up to 2 km; while Station Y may be located at a height of up to 10 km. Stations X and Y may be separated by a distance of up to 10 km. Windbags 30ap released from upwind Station X may be driven diagonally by the wind to downwind Station Y. Wind bags 30ap attached to tether lines 50ap may be connected to ground/or surface based generators 55ag. The capture of the wind current by means of windbag 30ap (drive unit 51); its power run from Station X to Y by the moving wind current being used to power generator 55ag (driven unit 55) to produce renewable electricity.

Spaced at regular intervals (distance of e.g. 100 m to 200 m apart) multiple wind bags 30ap may be run on a single pair of guide-lines 304ap (Lane Ap) at the same time. At the SOR point, a deflated incoming windbag 30ar from EOR point may be checked, prepared, and put on standby; ready to be deployed at the correct time. Wherein, said windbag 30aa may be refreshed by filling ring 22ap; air-ribs 277ap with compressed air; via the air inlet port 531 of apparatus 530; and released through the gates 520p; running from Station X to Station Y along guide lines 304ap'; 304ap"; pulling tether 50ap; powering generator 55ag. At Station Y windbag 30ap may be depowered and collapsed (air released from ring 22aa; air-ribs 277aa) via exhaust port 532 of apparatus 530. A piece of collapsible-extendable cylindrical/or, cone shaped plastic cover 536 tapered at one end may be pulled and slipped over the depowered windbag 30ar to keep it in a collapsed position for the return journey. Retract line 33ar located at point 32aa pulled to point 31aa and secured to clip 533 serves the same purpose. Inlet port 25ar ring 22ar may also be clipped shut by means of robotic limbs 522. Or, embedded string 23ar may be pulled taut to shut inlet port 25ar. The bag may then be routed to return guide-lines 304ar'; 304ar"; Lane Ar for retrieval by means of tether 50ar and retract motor 49ag from Station Y to X.

FIG. 6O illustrates a parallel seaborne system 510u; of the high altitude airborne wind energy harvesting system 510a

as disclosed in FIG. 6A to FIG. 6N above with some variations. Such a parallel system may comprise of: a floating semi-submersible Station U **292aa** located upstream; an underwater submerged Station V located downstream on the sea bed **537**; a floating semi-submersible Station W **292aa** located on the surface above Station V. Water-bags **40ap** may be launched on power generating runs from surface Station U to submerged Station V located on the sea bed **537**. Enabled by means of guide-lines **304ap'** and **304ap''** along run Lane Ap, Lane Bp, Lane Cp; etc. Sonar transmitter **299saa** may be used to activate depowering of water-bags **40ap** at the EOR phase; working in tandem with sonar receiver **298saa** mounted at inlet port ring **22ap** of bags **40ap**. Upon completion of the power run; the swivel rings **308ar'**; **308ar''** may be detached from guide lines **304ap'**; **304ap''** by means of robotic hands **522** and attached to retract lines **304ar**; and the bags **40aa** moved to surface transition Station W located above Station V. This may be enabled by means of air pockets **538** formed in cavity **19ar**; injected by robotic hand **522** held air nozzle **535**. At Station W the bridle lines **21aa** and bag **40aa** may be detached from line **50aa**. Line **50aa** are retracted to Station U at speed. The water-bags are stacked together, then retracted from Station W back to Station U by means of surface vessels **539** bearing stacks of water-bags **541** via pulley system **48aa** powered by HAV-400 wind crane. The bags are recycled and reused repeatedly.

Station V and Station W may be connected by a sub-system **540** for raising the submerged Station V from the seabed **537** to the surface level for servicing and repair works at intervals. And for lowering and reinstalling back Station V into its original location and position to continue working. System **540** may include motorized winches **59ap** (port); **59as** (starboard); loops of dual winching lines **542p'**; **542p''**; and **542s'**; **542s''**; seabed mounted pulley wheels **48ap** (port); **48as** (starboard); ballast tanks **543** (varying the amount of air to water content provides variable buoyancy); airbags **544**; mounting pillars **545** piled into the seabed **537**. Station V may be securely anchored to twin pillars **545** by means of designated slots, clamps, attachments, etc. Dual pairs of winch lines **542p'**; **542p''** and **542s'**; **542s''** may be used to connect Station V and Station W. At Station W winch lines **542p'**; **542p''** and **542s'**; **542s''** forms a loop around port winch **59ap** and starboard winch **59as**. The winch lines extends to two pulley wheels **48ap** and **48as** affixed to the seabed **537**; forming two complete loops. Line **542p'** and **542s'** extending from Station W may be securely affixed to the sides of Station V at points **546p** and **546s**; and continues on, looping through the pulley wheels **48ap** and **48as** until the lines portions (now indicated as) **542p''**; **542s''** reached winches **59ap**; **59as**.

Such a configuration enables Station V to be brought up to the surface for repair works. Ballast tanks **543** normally full of water may be filled up with air displacing the water; creating buoyancy for lifting Station V. Airbags **544** located between the seabed **537** and the bottom of Station V may also be filled up with air to create added buoyancy. Reducing the weight of Station V; such that winches **59ap** and **59as** may lift it up to the surface with ease. Ballast-tanks **543** and airbags **544** may be inflated by means of compressed air from storage cylinders **203aa** via air lines **204aa**; or by means of air lines **204aa** connected to surface based air cylinders **203aa** or a compressor located at Station W. This may be enabled by means of underwater drones **230aa** equipped with robotic limbs **522**.

Seaborne eco-system **300aa** may comprise of: power generation stations U; V; W; mooring buoys **508**; FPSO

vessel **511** with hydrogen generation plants **509**; atmospheric carbon-dioxide (CO2) capture plant **547**; diesel or methanol production plants **548** for manufacturing carbon neutral liquid fuels; tankers **296taa** with spherical tanks **549** for offloading hydrogen via transfer line **551**. CO2 derived from carbon capture and sequestration (CCS) projects may also be brought in by CO2 tankers to provide feedstock for liquid fuel production plants **548**. Tankers **296taa** and other ocean faring vessels may be powered by means of glider-drones HAV-400; or its variant HAV-400M. Anchoring lines **295aa** from the mooring buoys; semi-submerged columns **552** and submerged pontoons **553** of Station U; Station W; may be anchored by means of pillars **545** piled into the seabed **537**; or by means of suction cups **550** attached to the surface or floor of the seabed **537**. Station V may be affixed to piles and pillars **545** extending from the seabed **537**. Or, a subsea based Station V suspended in the sea below Station W may be anchored to the seabed piles using lines **295aa**. Spar mounted facilities may also be adapted for use where applicable.

The height of the stations (Station U; Station W) above the sea surface may be controlled by the flooding or de-ballasting of the ballast tanks inside the columns **552** (legs) and bottom pontoons **553** of the semi-submersible stations. Flooding of ballast tanks reduces its buoyancy; and the station sink deeper/lower. De-ballasting of ballast tanks increases its buoyancy; the station rises higher up. Such flexibilities may be used during maintenance of Station V. Station W may be lowered down near to the sea surface; then Station V may be raised up to the surface by means of winch lines **542p** and **542s**; buoyancy tanks **543** and lifting air bags **544**. Heavy duty chains may be used to link and attach the two stations together; one on top of the other. Station W may then be raised to a higher level by increasing the buoyancy of its ballast tanks. Thus enabling repair works to be carried out on Station V under dry dock conditions.

All phases of execution may be automated by means of an integrated system comprising: computerized smart artificial intelligence (AI); robotics; cameras; sensors; actuators; activation mechanisms; radio-frequency transmission; sonar transmission; remote sensing command and control systems.

FIG. 6P illustrates a variant reconfigured airborne windbags system **76av**; with improvements in productivity, efficiency; fuel savings; zero-carbon-pollution wherein a zero-emission vehicle (ZEV) comprising HAV-400 (drone navigation unit) spearheaded a multitude of windbags **30ap** in a power generating run; as compared to prior art system **76** (refer FIG. 5A of U.S. Pat. No. 8,963,362). HAV-400 replaces UAV-80 as drone navigation unit. FIG. 6Q illustrates the retraction phase of system **76av**. The navigation unit may consist of aerial drones comprising: glider drones; remote controlled drones; autonomous drones; or any type of suitable drones. Said drone navigation unit HAV-400 provides a means of directional control; guidance; powered flight if required to return to base. HAV-400 may be outfitted with winch **59aa**; with the winch line **33ap** affixed to point **229ap** on tether line **50ap**. The retract line **33aa** may be reconfigured to connect winch **59ap** (mounted inside HAV-400) via point **227ap** (on the outside of HAV-400's body) to point **229ar** on tether line **50aa**. Compressed air generated by the ram-air-turbine **71aa** of HAV-400 may be used to inflate ring **22ap** and air ribs **277ap** by means of an air-line **278aa** integrated with tether **50ap**. During the end of run (EOR) phase, gearbox **53ag** of driven unit **55ag** may be put on free gear; wherein said windbag **30aa** flows freely with the wind current exerting zero tensile force on tether **50aa**. HAV-400 may use winch **59ap** to wind back the retract line

**33ap** until point **229ap** coincides with point **227ap** on body of HAV-400. Optionally, it may turn on its propulsion system to fly a short distance to point **229ap**. A radio frequency transmitter (RF) **299raa** may be installed at point **229aa**. A radio frequency receiver cum RF signal homing device **554r** may be installed at point **227ap**. In case of retract line **33ar** failure; a radio-frequency transmitter **299raa** positioned at joint **229ar**; and a radio-frequency receiver cum homing device **554r** installed in the body of HAV-400 at point **227ar** may be used. Homing in on the RF homing signal coming from point **229ar**; HAV-400 flew towards **299raa** until points **227ar** and **229ar** coincides; and latches itself securely onto line **50ar** near to point **229ar** by means of specially configured and customized attachments comprising: hooks; rings; clips; grippers, etc. Wherein said multiple windbags **30aa**; **30ab**; **30ac** reversing direction behind HAV-400; are instantly depowered. As their aft joining point **32ap** faces fore, into the oncoming wind (W); while the fore bridle lines joining point **31ap** faces aft; as illustrated in FIG. 6Q. The glider-drone HAV-400 and line of depowered bags may then be retracted back to the start-of-run (SOR) point **16aa** by means of electric powered retract motor **49aa** which reeled back tether line **50ap**. Such an arrangement eliminates the need for a long retract line **33aa** all the way from the SOR point **16aa** to the EOR point **288aa**. And requires only a short portion of retract line **33ap** from point **229ap** to point **227ap** (and winch **59aa**) to be used. The inlet-outlet port **227ap** on the external body of HAV-400 allows retract line **33ap** to pass through to internal winch **59ap**. This modification totally eliminates the need for HAV-400 to fly all the way from EOR point **288aa** back to SOR point **16aa** under its own power. Thus saving fuel; eliminates carbon pollution; improving productivity and efficiency of the improved system **76ay**.

A variant reconfigured parallel underwater system **222av** using drone navigation unit UUV-230aa/or HAV-200aa may be used as a substitute for system **222** (refer FIG. 5A; U.S. Pat. No. 8,963,362); or to improve it. The reconfigured system **222av** may comprise of a modified zero-emission-vehicle (ZEV) UUV-230av equipped with pneumatic/or battery powered winch **59aa**; air tanks **203aa**; air lines **204aa**; **278ap** combined with tether line **50ap**; etc. The retract line **33ap** may be reconfigured and/or modified to connect winch **59ap** (mounted inside UUV-230av) via point **227ap** (inlet and outlet port) to point **229ap** on tether line **50ap**. A sonar transmitter **299saa** may be installed at point **229ap**. A sonar receiver cum sonar signal homing device **554s** may be installed at point **227ap**. In case of retract line **33ar** failure; a sonar transmitter **299saa** positioned at joint **229ar**; and a sonar receiver cum homing device **554s** installed in the body of UUV-230aa at point **227ar** may be used. Homing in on the sonar homing signal coming from point **229ar**; UUV-230aa propels itself towards **299saa** until points **227ar** and **229ar** coincides; and latches itself securely onto line **50ar** near to point **227ar** by means of specially configured and customized attachments comprising: hooks; rings; clips; grippers, etc. Hydrogen fuel cells (using hydrogen gas generated by eco-system **300aa**) and batteries may be used to provide electric propulsion for said ZEV drones; HAV-100aa; HUV-200aa; UUV-230av; HAV-400. Renewable fuels mix comprising methanol; biodiesel, etc. may also be used. Bottled compressed air from cylinders **203aa** may be used to inflate inlet port ring **22ap** and air ribs **277ap** by means of air-line **278aa** integrated with tether **50ap**. Two-way communications between the Control Center (command; execution signals) and the drone navigation unit

(feedback; status signals) may also be enabled by means of a hard wire communication line integrated with the tether line **50ap**.

FIG. 6R illustrates the use of naturally occurring reliefs and geological features on the seabed or the sea-floor **537** as anchoring points for securing lines **295aa** to anchor mooring buoys **508**; semi-submersible production stations U, W, **292aa**; floating flat-bed platforms **293aa**; inflatable floating bodies **294aa**; and other components of ecosystem **300aa**. Such geologic features may comprise seamounts **555** and islands **560**. Submerged seamounts **555** may comprise: guyots **556**; pinnacles **557**; knolls **558**; etc. Such that surface unevenness in the topography comprising: holes; indentations; protrusions; fissures; cracks; nooks and crannies, etc. of the seamounts **555**; submarine ridges **559**; trenches **561**; canyons; seafloor **537**, etc. may be adapted, modified and converted for use as anchoring points for securing lines **295aa**. By means of man-made apparatus comprising: piles **562** and pillars **546**; reinforced concrete beams **563**; cement plugs **564** inserted or built into artificial and/or natural caverns **565**; holes **566** drilled and artificial grooves **567** cut into suitable places of the rocky features of the seamounts **555** and islands **560**, etc. Such that anchor lines **295aa** may be secured to pillars **545** and piles **562**; lines looped around small hills, pinnacles **557** ridges **559**; lines looped through holes **566** held securely in recessed grooves **567**; etc.

FIG. 6S illustrates an enlarged view of a strategically located reinforced concrete beam **563** placed in position in between the V-shaped valley formed by two seamounts; a guyot **556** and a ridge **559** with the securing line **295aa** exiting from the opposite side of the V-shaped valley; for securing a floating body on the surface in position. Pillar and beam **563** may be locked in position by means of U-shaped piles **568** inserted into the seabed **537**. Also illustrated is an enlarged view of a reinforced concrete wedge **564** built inside a small natural or artificial cavern **565** with a narrow opening; with line **295aa** attached to the exposed tip of the conical/or pyramidal shaped cement plug **564**. All such modifications and adaptations shall be carried out with the least disruption to the existing natural ecosystem.

FIG. 6T to FIG. 6X illustrates system **570** for channeling sea water current by means of man-made sea walls **571p** (port) and **571s** (starboard); said walls **571** may be configured into a V-shaped apparatus. An inclined overhead ceiling **571c** may be used to divert water flow from above. Seafloor **537f** (floor) forms the bottom floor. A skid **572** of turbines **471** may be located at the V-shaped apex **569** where converging water flowed fastest due to constriction caused by the walls of the apparatus **570**. A large inlet port converging the water to flow through a small constricted outlet or port. Wherein said skid **572** comprising a multitude of water turbines **471** may be used to harvest the kinetic energy of the high speed water current efficiently. Optionally, said apex **596** may be configured as a tunnel-like structure **569t**; into which a specially configured seaborne hydro-electric generation tunnel **575** carrying a plurality of large turbines **471** units may be slotted/or inserted.

FIG. 6T illustrates the plan view of a funnel shaped configuration of sea walls **571**; while FIG. 6U illustrates the perspective view. Water intake port **573** of apparatus **570** may be protected by a cage and mesh **573c** which acts as a filter keeping out marine wildlife. FIG. 6V illustrates the front view of an individual turbine **500b** mounted in a square shaped frame **574**. FIG. 6W illustrates the perspective view of a skid **572** of turbines **471**. This structural configuration enables a plurality of turbines **471**; **500b**; etc. to be slotted into and stacked up in the skid **572**. One unit on top of

another. Wherein, rows upon rows; stacks upon stacks of turbines may be arranged inside said skid **572**. Apparatus **570** and skid **572** may be anchored to the sea floor by means of pillars **545** or piles **562**. The whole skid **572** may be installed/or removed by means of winches **59as**; **59ap**; 5  
mounted on semi-submersible Station W **292aa**; or by means of floating crane barges for periodic maintenance.

FIG. 6X illustrates a variant configuration wherein said apex **569** may be configured as a tunnel-like structure **569t**; 10  
with a flip-able top roof cover. Such that this top roof cover may be flipped open or close; and secured in place. A specially configured seaborne hydro-electric generation tunnel **575** containing a plurality of large water turbines **471**; or **500b**; etc. may be slotted into/or removed from the flip-able top roof cover of tunnel **569t**. Such that apparatus **575** may be lowered into tunnel **569t** during installation; or lifted out 15  
by means of semi-submersible Station W **292aa**; or crane barges for maintenance. A central shaft **576** for mounting said plurality of turbines may be configured in the center supported by peripheral beam **575s**. Shaft **576** may be split 20  
into sections **576a**; **576b**; **576c**; and configured for separate operation of each individual turbine units. The rotational movement of the turbine unit **471a** may be transmitted from the individual horizontal shaft section (e.g. **576a**) to an angular transmission gear box **476u**; to vertical shaft **475u**; to generator unit **577a**. Submarine cable **457u** may be used 25  
for transmission of power generated to shore or surface vessels **511**.

FIG. 6Y illustrates system **580**; a plurality of water turbines suspended in the sea. A mooring buoy **508**; or, a floatation-ballast tank **578** on the sea surface enables line **457u** to hold the submerged turbines **471**; **500a**; **500b**; in place while the other end of line **457u** may be anchored to the sea floor by means of a suction cup device **550**; or to other means such as piles **562**. Top surface of tank **578** may incorporate solar cells **579** for generation of electricity to power navigation lights and RF signals. The body of turbines **471**; **500a**; **500b**; may be outfitted with swim control surfaces comprising: fins, planes **205aa**; **207aa**; stabilizers **208** to keep them in proper orientation. Optionally, the whole apparatus comprising: the ballast tank **578** and line of turbines may be configured to be totally submerged below the sea surface. In order to avoid hazards posed by surface ships. This may be effected by means of: air tanks **203aa**; air-lines **204aa**; and an automated system for buoyancy control of ballast tank **578**. 35

All critical components of the above water-turbines; their electrical generation and transmission systems, etc. may be enwrapped in an impervious layer of cover/or protective materials. Such materials may comprise plastics; polymers; fiber-glass; carbon composites; poly-ethylene; poly-propylene; etc. Such protective materials for insulation of electrical components and corrosion prevention may be sprayed-on, applied as a coating, wrapping, embedded, impregnated, etc. 50

Normally renewable energy generation may be associated with a distributed network for direct extraction and generation of electrical power. However, in a variant configuration renewable energies extracted by a multitude of drive units **51aa** may also be congregated into integrated driven unit **585a**; **585b**; **585c**; comprising a centralized generation plant **585** for production of electricity as illustrated from FIG. 7A to FIG. 7H. 55

FIG. 7A to FIG. 7H illustrates system **600** comprising: (a) A Distributed System for Extraction of Energies from high altitude wind currents and deep sea ocean currents by means of drive units **51aa**; (b) a tensile force transmission system for channeling and transmitting this extracted energies to a; 65

(c) utility scale Centralized Power Generation Plant **585**. Said generation plant **585** comprises: driven unit **584a**; **584b**; **584c**; line reel drums **582**; gearboxes **583**; clutch boxes **587**; retract motors **589**; for producing renewable electricity; wherein, variant driven units may include counter-rotational generators **590d**; **590h**. The energies transmitted may be converted into other forms of energy; or for doing other useful work.

FIG. 7A illustrates a single drive unit **51aa** comprising of: 10  
a plurality of drones HAV-**400s** linked in series flying one on top of another; connected by a single tether **50aa** to generator **55ag**. Combined use of such a multitude of airborne glider-drone HAV-**400** wind-cranes produces a much more powerful lifting force to power generator **55ag**; than a single unit. Such a configuration may also be used to power the systems of centralized power generation plant **585**.

FIG. 7B illustrates system **600** comprising of: a centralized power generation plant **585** connected to and powered by a multitude of high altitude wind energy extraction apparatus made up of drive units **51aa** comprising: HAV-**100aa**; windbags **30aa**; HAV-**400**; windbags system **76av**; morphing kite-glider-drone vehicles HAV-**400M** armed with windbags and wing-suits **30aa**. The generation plant **585** may comprise of a plurality of driven units **585a**; **585b**; **585c** connected to a single common shaft **581**. Wherein, said driven units **585a**; **585b**; **585c** may be powered by a plurality of drive units: **51aa**; **51ab**; **51ac**; etc. The common shaft **581** linked together all components of the plurality of driven units **585a**; **585b**; **585c**. Wherein, an individual driven unit **585a** may comprise: line reel drum **582**, gearbox **583**, generator module **584a**; bearing boxes **586**; clutch box **587**; retract motor **589**. Said plurality of driven units **585a**; **585b**; **585c** may be configured to move in unison with each other in a single direction of rotation (stators-rotors configuration); just like conventional generators the world over. 35

A variant configuration allows and enables each individual driven unit (e.g. **585a**; **585b**; **585c**) to move in different directions of rotation. Wherein, said main shaft **581** may be adapted into individual section **581a**; **581b**; **581c**; etc. Such that each said section **581a**; **581b**; **581c**; may be connected together; or segregated from each other by means of an apparatus **587**. Working like a simplified vehicle's clutch-gear system; apparatus **587** may be used to link and connect two shaft sections (e.g. **581a**; **581b**) together when it is shifted into an engaged position. When it is shifted into the neutral position (freed), apparatus **587** disengages this linkage; breaking the connection between the two sections (e.g. **581a**; **581b**); allowing them to rotate freely and turn independently of each other. Apparatus **587** may be also be integrated with gearbox **583** into a single unit; such that a particular drive unit may be engaged; or disengaged as and when required (refer FIG. 7C). Such flexibility enables the use of counter-revolving generators comprising **590d**; **590h**. For example: driven unit **585a**; driven unit **585c** mounted in section of shaft **581a**; **581c** may be configured to rotate clockwise; whereas driven unit **585b** mounted in section of shaft **581b** may be configured to rotate anti-clockwise. Such that said opposing directions of rotations may be used to power variant generator modules such as: **590d**; **590h**; configured with dual counter-rotating rotors comprising: rotor wire coils and rotor magnets. 50

FIG. 7C illustrates details of FIG. 7B wherein the line reel unit **582**; gearbox unit **583** and clutch unit **587** may be integrated together as a single unit; powering the generator **584** by means of main shaft **581**. The combined unit **585** may be assigned new identifying numbers: line reel drum (**582**); gear box (**583**); retract motor (**589**). Retract motors 55

49ag may be directly connected to the line reel drums 582 (bypassing the common shaft 581) and identified as 589.

FIG. 7D illustrates system 600; a variant driven unit 585d configured with a variant vertically disposed twin rotating discs generation unit 590d'; 590d"; 590d'''. FIG. 7E illustrates details of FIG. 7D. Driven by a plurality of drive units 51aa via shaft 581; said double discs comprising: rotor coiled wire disc 486; rotor magnet disc 487; turning in opposite directions; counter rotates against each other to generate electricity (refer FIG. 4E; FIG. 4F). Generator 590d of FIG. 7E may be used in the centralized power plant 585 to generate electricity. Wherein, said individual driven units 585d'; 585d"; 585d'''; associated with individual sections of shaft 581'; 581"; 581'''; may be connected to and powered by a multitude of: (a) high altitude flying wind energy extraction apparatus made up of drive units 51aa comprising: HAV-100aa; 30aa; HAV-400; HAV-400M; windbags 30aa system 76av; and (b) deep-sea diving water energy extraction apparatus made up of drive units 51aa comprising: HUV-200aa; water-bags 210aa; water-bags 40aa system 222av. The drive units 51aa may be linked to the driven units 585d'; 585d"; 585d'''; by means of: (a) pulley wheels 48aa; (b) line reel drums 582; (c) dual line reel drums 582 cum 588 with transmission lines 591 protected by hard cover 592. This system of using auxiliary apparatus enables drive units 51aa to be distributed at an extended range/or a long distance away from the centralized generation plant 585. Providing an extended range and an enlarged area/or volume for extraction of airborne and waterborne energies.

FIG. 7F illustrates a variant line reel spool 582 in which dual units of line reel drums 582; 588; may be joined together with a shaft 593; and bearing boxes 586 mounted on a supporting body frame 594. Line reel drum 582 may be loaded with tether lines 50aa. While line reel drum 588 may be purposely kept empty; and linked to line reel drum 582' (full drum). Such that when the lines are transferred from drum 582' to drum 588; drum 588 may be fully loaded with transmission lines 591 from drum 582' (refer FIG. 7D, drive unit 222av). Such auxiliary apparatus may be used as a transfer mechanism for intermediate energy transmission between the drive units 51aa and driven unit 581a; when the two units may be separated by a long distance, e.g. 3-5 km apart.

FIG. 7G illustrates system 600; a variant driven unit 585h configured with a variant horizontally disposed twin rotors generation unit 590h. FIG. 7G also illustrates the combined use of auxiliary apparatus (a) to (c) disclosed in FIG. 7D above; together with: (d) extended transmission shafts 595; (e) and a variant angular transmission gear box 583v; etc. in the extraction of wind and water energies from an enlarged area/or volume of the natural ecosystem. Such apparatus may be used to overcome physical obstructions caused by hills, cliffs, corners, sharp bends, etc. and improve operational flexibility and dexterity. The extended transmission shafts 595; and tensile force (energy) transmission lines 591 running in between line-reel-drums (LR1) 582'; (LR2) 582"; (LR3) 582''' and the gear boxes 583; 583v; may be covered by conduit pipe 592 for safety purposes.

The following description on the port side of generator 590h; main shaft 581p; illustrates combined use of the plurality of line-reel-drums: 582'; 582"; 582'''; powered by HAV-400. For simplicity the drums may be referred to as: LR1; LR2; LR3. The LR1 comprises of normal line reel drum 582' fully loaded with tether line 50aa. LR2; LR3; and lines 591 in between them may comprise the tensile force transmission system. To start with, LR1 may be loaded full of line 50aa. LR2 may be empty; LR3 may be loaded full of

lines 591. Operation of said plurality of line-reel-drums: 582'; 582"; 582'''; for transmission of tensile force produced by HAV-400 on tether line 50aa to generator 590h may be described in the following steps: Tensile force on tether line 50aa may be transmitted by means of pulley wheels 48aa' and 48aa"; causing LR1 to rotate. This rotational movement is transmitted from LR1 to LR2 by means of extended transmission shaft 595'. This causes empty LR2 to wind in lines 591 from the fully loaded LR3; causing LR3 to rotate. LR3 then transmitted this tensile force by means of extended transmission shaft 595" to gearbox 583p; which transmitted this tensile force to the port side main shaft 581p; causing it to rotate. This shaft rotation is transmitted to generator 590h; causing the rotor wire coil 474 to rotate.

The following description illustrates use of a plurality of extended transmission shafts 595; gearboxes 583 and a variant angular transmission gearbox 583v; for transmitting the tensile force produced by HUV-200aa to generator 590h (port side; shaft 581p). Tensile force generated by HUV-200 may be transmitted by means of: the tether line 50aa to line reel drum 582 via pulley system 48aa; causing drum 582 to rotate. This rotational movement may be transmitted by means of extended transmission shaft 595a to variant gearbox 583v; then to gearbox 583p" by means of extended transmission shaft 595b; then to gearbox 583p' mounted on main shaft 581p by means of extended transmission shaft 595c. Gearbox 583p' then transmitted this torque to shaft 581p; which is then transmitted to generator 590h; causing the rotor wire coil 474 to rotate.

Drive units HAV-400 and HUV-200aa may take turn to run. When one drive unit is working; the other may be retracted and put on stand-by. Similarly, drive units HAV-100aa and HAV-400 located on the starboard side of generator 590h; main shaft 581s; takes turn to operate to power generator 590h; causing rotor magnet 476 to rotate. The counter-rotation of said rotor wire coil 474 and rotor magnet 476 enables utility scale generator 590h; and thus the Centralized Power Generation Plant 585 to produce renewable electricity. Instead of two alternate drive units on each of the port and starboard side of generator 590h; multiple units may be configured and sequenced to run providing much more powerful torque for 590h.

Such a tensile force transmission system comprising: energy transmission tools, equipment and apparatus provides an enabling means for operation of system 600. A system for harvesting energies from the natural environment by means of a multitude of distributed apparatus; and the transmission of this collected energies; to a central power plant 585 for generation of renewable electricity.

FIG. 7H illustrates details of FIG. 7G. Driven by a plurality of drive units 51aa via shaft 581p; 581s; said double rotors generator comprising: rotor wire coil 474; rotor magnet 476; may be configured to turn in opposite directions; counter rotating against each other to generate electricity (refer FIG. 4C; FIG. 4G). If the wire coil 474 rotates clockwise; then the magnet 476 rotates anti-clockwise. Or, vice-versa. Both of the rotors comprising: wire coil 474 and magnet 476 may be individually connected to the shaft 581p (port side); 581s (starboard side) and powered by its own dedicated drive units. Port side drive units 200aa and 400 may be connected directly to the shell mounted wire coil 474 by means of shaft 581p and yoke 484p. Wire coil 474 may be supported on the starboard side by yoke 484s and bearing ring 596. While the starboard side drive units 100aa and 400 may be connected directly to the center mounted electro-magnet 476 by means of starboard side shaft 581s. Generator 590h may comprise of rotor wire coil 474; rotor

magnet **476** linked by individual sections of shaft **581p**; **581s**; wherein, said sections **581p**; **581s** may be held in position by means of a bearings **597** sleeve **598**. Such that even though sections of shaft **581p**; **581s** may rotate in opposing directions; they may be aligned with each other. The sections **581p**; **581s**; may be supported by a plurality of bearing boxes **586** affixed to pedestals **599**. Generator **590h** may be protected by external body cover **473**; and mounted on a solid base **594**. Compared to conventional rotor-stator generators, such a counter-rotating configuration of system **590h** enables much higher efficiency and productivity. As the speed and movement of the generating surfaces of both rotating elements relative to each other may be doubled. A variable electrical (or magnetic flux) controller **466** may be used to vary the supply of current to the electro-magnet **476** of the generator; and thus vary the production of electricity relative to the wind power available at the point in time.

Conventional combined cycle power systems typically have a primary drive unit to power a stator-rotor generator; then use the exhaust flue gas; (or recover the heat energy by generating steam) for powering a secondary drive unit cum generator.

FIG. **71** illustrates a variant combined cycle power generation plant using a counter-rotating generator **590h**. Input to the primary drive unit **601** comprising fuel; high pressure steam; etc. may be routed by means of pipe **602**. Wherein, the exhaust flue gas; or steam from primary drive unit **601** located on the starboard side of said generator **590h**; may be routed via pipe **603** to the secondary drive unit **604** (located on the port side) to drive said generator **590h**. Such that the primary drive unit **601** drove the rotor magnet **476**; while the secondary drive unit **604** drove the rotor wire coil **474**. After drive unit **604**; the exhaust may then be routed via pipe **605** to the tertiary drive unit **606** for driving a steam turbine-generator; or flue gas turbine-generator to produce power. Or a waste heat generator to produce low pressure steam or hot water.

FIG. **8A** illustrates a variant submerged system **570u** of FIG. **6T** to FIG. **6X**; wherein a reconfigured water-bag **40aa** may be integrated with a seaborne hydro-electric power generating tunnel **575v** for producing renewable energy. Tunnel **575v** may be similar in purpose to the penstock of a HEP dam. Water-bag **40aa** may be used as a funnel to entrap the flow of sea water; concentrate this large flow of water into a constricted tunnel **575v** fitted with a plurality of turbines **471** to generate electricity. Turgid inlet port ring **22aa** and water-ribs **277aa** kept water-bag **40aa** in functional shape. The light-weight tunnel **575v** made of fiberglass; carbon fiber; Kevlar, plastics, etc. may be and attached to a semi-submersible Spar buoy **607** on the water surface. The bottom portions of the submerged water-bag **40aa** and the power generating tunnel **575v** may be securely anchored by means of a plurality of lines **295aa** to the seabed **537**; seamounts **555** comprising: ridges **559**; beams **562**; plugs **564** inserted into cavern **565**; holes **566** with grooves **567**. The while the upper portions may be anchored to floating buoys **508** on the sea surface and/or submerged ballast tanks **579** by means of lines **457u**. Fishing nets **573c** may be used to keep out marine wildlife. Electricity generated by the seaborne hydro-electric power generating system **570u** may be routed by means of cable lines **457** to ground stations on shore/or, to mooring buoy **508**; FPSO **511** equipped with electrolyzer plants **509**; ecosystem **300**.

FIG. **8B** illustrates a parallel airborne system **570a**. Such a system may also be configured and used for airborne deployment of windbags **30aa**. Wherein, similar to the underwater system **570u**; said airborne system may com-

prise of a plurality of glider-drones HAV-**400**; HAV-**400M** wind-cranes carrying aloft a large windbag **30aa** connected to a light-weight tunnel **575** bearing a plurality of turbines; by means of a plurality of tether lines **50aa** and mooring lines **46aa**. Inflated inlet port ring **22aa** and air-ribs **277aa** kept windbag **30aa** in functional shape. The upper portions of the windbag **30aa** and tunnel **575a** may be lifted up by means of a plurality of tether lines **50aa**; bridle lines **21aa** attached to a plurality of HAV-**400s**; balloons filled with LTA gases; etc. While the bottom portions may be anchored to a plurality of boats **220aa**; mooring buoys **508**; semi-submersible Spar buoy **607** on the sea surface. On land the system may be secured to the ground; adapted hills; mountains and valleys by means of a plurality of tether-cable **478** and piles specially inserted for mooring the system. Electricity generated by the airborne aero-electric power generating system **570a** may be routed by means of tether-cable **478** to ground stations/or to mooring buoy **508**; FPSO **511** equipped with electrolyzer plants **509**; a combined ecosystem **500** and **300**.

FIG. **8C** illustrates a system wherein, a plurality comprising pieces or strips of fabric materials **415b** may be carried aloft by means of a plurality of light duty glider-drones HAV-**400**; or HAV-**400M** wind cranes. A variant system of power kites gliders **400v**; or kite drones **400v** which use only wind energy to generate aerodynamic lift; tether **50aa** and mooring lines **46aa**; may also be used. Said strips of light-weight materials may comprise solar fabrics **415b** for harnessing solar energy to generate renewable electricity. Such materials may be mounted on a layer of aero-foams **608**; light weight foams filled with bubbles/or pockets of lighter-than-air gases: comprising helium; hydrogen; etc. Such that said pieces of aero-foams **608** may be buoyant to a certain degree due to the presence of LTA gases used in its manufacture; light-weight; and maintains its physical shape. Multiple strips of such aero-foams bearing solar fabrics **415b** may be joined together by means of lines **609** forming an airborne flying carpet for harnessing solar energy. A plurality of lines **609** may also be used by a plurality of HAV-**400** to lift the apparatus up. Gaps of empty space left in between said strips of interlinked aero-foams **608** cum solar fabrics **415b** allows passage of wind current. Power generated may be channeled by means of cable-tether **478**. Such light weight aero-foams **608** and solar fabrics **415b** may also be used on water surfaces as floating solar energy collectors as illustrated in FIG. **8D**.

Whenever and wherever practicable all activities, equipment, vessels, etc. of present invention shall be powered by means of zero-carbon energies generated by the bagged power generation system. All activities would be carried out in compliance with relevant government regulations; international protocol; IPCC requirements; in consultation with NGOs; environment groups, etc. expediting change-over of our present carbonaceous; hydrocarbon based economy to a clean hydrogen—electrified economy powered by renewable energies.

Global climate change is a man-made catastrophe. Therefore, this existential threat may be aggravated or mitigated dependent upon: human decisions; actions and reactions. CO<sub>2</sub> caused climate change is bad enough. The main danger lies in the hijack of climate change by methane gas emissions—from the deep-sea methane hydrate deposits; Arctic and Antarctic methane hydrate deposits; stored underground for millions of years. When CO<sub>2</sub> induced global warming heated up these stored deposits of carbon; causing their inadvertent release into the atmosphere. That may well be the start of human extinction. What? Mankind—to follow

the dinosaurs into extinction; history? And this is (may) already (be) happening! Because methane gas is 100 times more potent than CO2 in its first ten year period. It is 20 times more potent over a 100 years period. Another gas that accompanies methane release in smaller quantities, nitrous oxide N2O is 300 times more potent than CO2. Humans must use our own personal knowledge; common sense; judgment; moral and religious values; in our search for answers to questions in which we may not be experts. Scientific papers; peer reviewed documents; climate data; Paris Climate Accord; etc. may provide more information. Internet searches may include phenomena such as: "methane bubbles in Arctic lakes"; "methane blow holes"; "exploding pingo"; "trembling tundra"; "7000 under-ground methane gas bubbles poised to explode in the Arctic"; methane gas bubbles trapped in ice in Alaska, tundra; Arctic expeditions; surveys of Centre for Arctic Gas Hydrates and Environment (CAGE); "SWERUS"; undersea methane flares; etc.

Mission-Vision Statement: To reduce; eliminate Global Warming; to save our spaceship—Planet Earth from the dangerous effects of Global Climate Change! The use of drones to serve humanity! To produce clean energy; to preserve clean air and clean water for all of us! We must always remember this; that we only have:

One race—Humanity! One planet—Earth! One common Destiny!

We must all work hard to preserve; not destroy, our one and only "live support system"—Earth's biosphere! For in the fate of mother Earth; and in our own hands, lies our common destiny—for all things living on this planet; and future generations of—plants; animals; humans. It is our common duty and responsibility to do our part: innovators, entrepreneurs, financiers, governments and NGOs, etc. To Save The World, Our World! "Look high, look far. Our aim the sky, our goal the stars!" To an inventor the sky's the limit.

While the preferred embodiments of the devices and methods have been described in reference to the environment in which they were developed, they are merely illus-

trative of the principles of the inventions. The elements of the various embodiments may be incorporated into each of the other species to obtain the benefits of those elements in combination with such other species, and the various beneficial features may be employed in embodiments alone or in combination with each other. Other embodiments and configurations may be devised without departing from the spirit of the inventions and the scope of the appended claims.

The invention claimed is:

1. A system for generation of electrical power by means of a flying energy generator lofted into altitude comprising:
  - a drive unit (51) comprised of an unmanned aerial drone (80; 100), first and second tether lines each having a first end and a second end, and a retract line having a first and second end, the first ends of the first and second tether lines attached to the unmanned aerial drone and the second ends of the first and second tether lines attached to the retract line, the retract line further includes a plurality of windbags connected in series to the retract line;
  - a driven unit (55) having a body that includes a generator (54), the driven unit attached via the second tether line to the unmanned aerial drone where the first end of the second tether line is attached to the generator and the second end of the tether line is attached to the second end of the first tether line and the second end of the retract line;

wherein tensile force exerted on the windbags by the air water current is transferred via the tether line to the driven unit to generate energy;

wherein the aerial drone controls the system and depowers the system by turning the retract line.
2. The system of claim 1 wherein the driven unit further includes a line reel drum (52), a gearbox (53), a retract motor (49), and means for supporting the driven unit, wherein the retract motor is operable to reel in and retract back the second tether and windbag and the drive unit is adapted to turn the retract line.

\* \* \* \* \*